



Mokuzai II™ captures a timber-inspired design in a porcelain tile. Through high-definition printing, vivid detail is used to achieve appealing wood tones in large format planks.

MOKUZAI II™

Glazed Porcelain



FLOOR / WALL



RESIDENTIAL



COMMERCIAL



INDOOR



OUTDOOR



POOL



Hikari



Daku



Shiro



Gure



Oxford

Sizes Thickness Faces Finish Edge Grout Joint Recommendation							
	8" x 35" 7.87" x 35.43"						
	10mm						
	9						
	Matte						
	Pressed						
Testing	Abrasion Resistance C1027	Breaking Strength C648	Chemical Resistance C650	Water Absorption C373	DCOF ANSI A1371	Scratch Hardness MOHS	Shade Variation Rating
Results*	IV	>500 lbf	Resistant	<0.50%	>0.55	7	V2

Product and Installation Details | ANSI A108.02
 Section 4.3.8.2 - For running bond/brick jointing patterns utilizing tiles (square or rectangular) where the side being offset is greater than 18" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the tile manufacturer. If an offset greater than 33% is specified, specifier and owner must approve mock-up and lippage.



Sustainability Attributes

- Red List Free
- Health Product Declaration (HPD) provided upon request
- Product Packaging is 100% recyclable
- VOC Free
- Recycled Content 0% Post-Consumer

*For more information visit www.emser.com. Always consult a professional for proper usage and installation.