

16-Channel Hybrid DVR



Key Features

- Supports H.265/H.264 video formats
- Supports audio over coaxial cable (only for TVI cameras)
- Supports TVI, AHD, CVI, CVBS, IP cameras with adaptive access
- 16-channel BNC input
- Supports 1-ch CVBS output, 1-ch VGA output, 1-ch HDMI output up to 4K(3840 x 2160)
- HDMI and VGA simultaneous output
- Long transmission distance over coaxial cable
- Supports mainstream cameras of ONVIF and RTSP protocols

Specifications

Model	DVR16.3		
Video/Audio Input			
Analog Video Input	16-ch, BNC		
IP Video Input	8-ch(only IP up to 24ch), each channel up to 8MP		
	Supports AHD input:		
	8MP@15fps		
	5MP@20fps		
	4MP@30fps		
	1080P@30fps		
	720P@60fps		
Supported Analog	Supports TVI input:		
Camera Types	8MP@15fps		
	5MP@20fps		
	4MP@30fps		
	1080P@30fps		
	720P@60fps		
	Supports CVI input:		
	8MP@15fps		

 		 - M D \ /
	N A + N	BY.
	$I \vee I \mid I \setminus A$	MSTR

DATASHEET

		DITION			
	5MP@25fps				
	4MP@30fps				
	1080P@30fps				
	720P@30fps				
	Supports CVBS input				
Audio Input	1-ch, RCA				
Audio Compression	G.711U				
Video/Audio Output					
CVBS Output	1-ch, BNC				
VGA Output	1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz				
HDMI Output	4K(3840X2160)/30Hz, 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz				
Audio Output	1-ch, RCA				
Synchronous Playback	16				
Live view display	HDMI/VGA: 1/4/6/8/9/16/25				
Two-way Audio	1-ch, RCA				
Network					
Incoming Bandwidth	80Mbps (Up to 112Mbps after all analog channel conv	ersion)			
Outgoing Bandwidth	160Mbps				
Remote Users	128				
Protocols	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, D	NS, DDNS, SMTP			
	IE(IE10/11) for Windows				
_	Firefox (version 52.0 and above) for Windows				
Browser	Chrome (version 45 and above) for Windows				
	Edge (version 79 and above) for Windows				
Encoding					
Recording Resolution	8MP Lite/5MP Lite/4MP Lite /1080P/720P/D1				
	Main stream	Sub stream			
	8MP Lite@8fps	D1@8fps			
	5MP Lite@12fps	D1@12fps			
Recording Frame Rate	4MP Lite@15fps	D1@12fps			
	1080P@15fps	D1@12fps			
	720P@30fps	D1@12fps			
Audio Sample Rate	8KHz,16 bit per channel				
Audio Bit Rate	64Kbps per channel				
Decoding					
-	Analog: 16 x 8MP Lite@8, 16x 5MP Lite@12, 16x 4MP Lite@15, 16 x 1080P@15, 16 x 720@30				
Capability	IP: 24 x D1@30, 16 x 720P@30, 8 x 1080P@30				


ILLL	JMIVUE MSTR DATASHEET			
Hard Disk				
SATA	2 SATA interfaces			
Capacity	Up to 8TB for each HDD			
	(The maximum HDD capacity varies with environment temperature)			
General Alarm				
General Alarm	Motion detection			
Alert Alarm	IP Conflict, Network Disconnected, Disk offline, Disk Abnormal, Illegal Access, Hard Disk Space Low, Hard Disk			
/ Wer e / Warm	Full, Recording/Snapshot Abnormal			
External Interface				
Network Interface	1 RJ45 10M/100M/1000M self-adaptive Ethernet Interface			
USB Interface	Rear panel: 1 x USB3.0, Front panel: 1xUSB2.0			
Serial Interface	1 x RS485			
Alarm In	4			
Alarm Out	1			
General				
Power Supply	12V DC			
	Power Consumption: ≤ 12 W (without HDD)			
Working Environment	-10°C~+ 55°C (+14°F~+131°F), Humidity ≤ 90% RH (non-condensing)			
Dimensions(W×D×H)	380mm ×326mm× 53mm (15.0" × 12.8"×2.1")			
Weight (without HDD)	≤2.0 Kg (4.4lb)			
Certification				


UL /CE /FCC /RoHS /WEEE

Certification




Dimensions





Rear Panel



Warranty

All Illumivue products come with a 3-year limited liability warranty. This warranty includes parts and labor repairs on all components found to be defective in material or workmanship under normal conditions of use. This warranty shall not apply to products which have been abused, modified, or disassembled. Warranty items only by authorized resellers. Warranty not eligible for products purchased through non-authorized online sellers.

A product that fails under conditions other than those covered will be repaired at the current price of parts and labor in effect at the time of repair. Such repairs are warranted for 90 days from the date of reshipment to the buyer. If the unit is delivered by mail, customers agree to insure the unit or assume the risk of loss or damage in transit. Under no circumstances will a unit be accepted without a return authorization number. The warranty is in lieu of all other warranties expressed or implied, including without limitations, any other implied warranty or fitness or merchantability for any particular purpose, all of which are expressly disclaimed. Proof of sale may be required in order to claim warranty.