




DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITY TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



REF NO.:

DWG31854

DESCRIPTION:

22-400 Metal Screw Cap, Teflon Liner

TEFLON LINER SPEC

PRODUCT: General Purpose Virgin Electrical Grade PTFE

PART NUMBER: TP102; SF102; SK102; ST102

COMPOSTITION (% BY WEIGHT): 100% Virgin PTFE

PROPERTY	TEST METHOD	UNITS	VALUE
Specific Gravity	INTERNAL	g/cm ³	2.15 – 2.19
Tensile Strength	ASTM D 4894	Mpa	19.31 MIN
Tensile Strength	ASTM D 4894	PSI	2800 MIN
Elongation	ASTM D 4894	%	225 MIN
Dielectric Strength	ASTM D 149	V/mil	500 MIN
Hardness	ASTM D 785	Shore D	55
Flammability Rating	UL 94		94 V-0
Continuous Operating Temperature	ASTM D 4591	kJ/kg. K (Btu/lbs/°F)	260°C (500°F)
FDA 21 CFR part 177.1550			COMPLIANT
3-A Sanitary Standards, Number 20-17			COMPLIANT
Material Shelf Life			INDEFINITE