

Product: [734A12](#) 



DS3/DS4 Central Office Coax, 12 x RG-59, 20 AWG Solid BC, Foil + 85% TC Braids, PVC Inner & Outer Jkts, CMR

Product Description

DS3/DS4 Central Office Coax, 12 Coaxes, RG-59, 20 AWG Solid Bare Copper Conductor, PE Insulation, Foil + 85% Tinned Copper Braid Shields, PVC Inner and Outer Jackets, CMR

Technical Specifications

Product Overview

Suitable Applications:	Central office wiring, DS3/DS4 interconnect, 734/735 telecommunications systems, switchboard communications
------------------------	---

Construction Details

RG Type:	59
----------	----

Conductor

Size	Stranding	Nom. Diameter	Material
20 AWG	Solid	0.032 in	BC - Bare Copper

Insulation

Material	Nom. Insulation Diameter
PE - Polyethylene (Foam)	0.148 in (3.76 mm)

Inner Shield

Layer	Shield Type	Material	Material Trade Name	Coverage
1	Tape	Bi-Laminate (Alum+Poly)	Beldfoil®	100%
2	Braid	Tinned Copper (TC)		85%

Inner Jacket

Material	Nom. Diameter
PVC - Polyvinyl Chloride	0.235 in (5.97 mm)

Inner Jacket Table Notes:	Each jacket gray and numbered
---------------------------	-------------------------------

Outer Jacket

Material	Nom. Diameter
PVC - Polyvinyl Chloride	1.07 in (27.2 mm)

Electrical Characteristics

Return Loss

Frequency	Min. Return Loss
15 - 95 MHz	30 dB

Attenuation

Frequency	Max. Attenuation
5 MHz	0.6 dB/100ft
10 MHz	0.8 dB/100ft
22.5 MHz	1.3 dB/100ft
50 MHz	1.8 dB/100ft
100 MHz	2.8 dB/100ft

200 MHz	4.0 dB/100ft
---------	--------------

Electricals

Nom. Conductor DCR	Nom. Inner Shield DCR	Nom. Capacitance Cond-to-Shield	Nom. Characteristic Impedance	Nom. Velocity of Prop.
10 Ohm/1000ft (33 Ohm/km)	2.4 Ohm/1000ft (7.9 Ohm/km)	16.8 pF/ft (55.1 pF/m)	75 Ohm	82%

Voltage

UL Voltage Rating
300 V (CMR, CMG)

Mechanical Characteristics

Temperature

Operating
-30°C to +75°C

Bend Radius

Installation Min.
1.0 in (25 mm)

Max. Pull Tension:	485 lbs (220 kg)
Bulk Cable Weight:	436 lbs/1000ft (649 kg/km)

Standards and Compliance

Environmental Suitability:	Indoor - Riser, Indoor
Sustainability:	CA Prop 65
Flammability / Reaction to Fire:	UL1666 Vertical Shaft
NEC / UL Compliance:	CMR
CEC / C(UL) Compliance:	CMG
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), REACH, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

History

Update and Revision:	Revision Number: 0.422 Revision Date: 09-07-2025
----------------------	--

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC	Footnote
734A12 008500	Gray	Reel	500 ft	612825184140	C
734A12 0081000	Gray	Reel	1,000 ft	612825184171	C

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.