



We Know Water.

OUTDOOR RATED VANDAL RESISTANT UNIVERSAL BARRIER-FREE VERSACOOLER® II

• PGVD8ACSL • PGVDACSL

Suggested Specification

Model PGVD8ACSL shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing. Model PGVDACSL is a non-refrigerated fountain and delivers ambient water. Shall include a single vandal resistant push button to activate the flow of water. Basin shall be designed to eliminate splashing and standing water. Water saver bubbler reduces waste water by 50% and shall operate between 20 and 100 PSI. One-piece vandal resistant metal bubbler keyed into place to prevent vandalism. Cabinet finish shall be brushed stainless steel. Cabinet shall have perforated galvanized steel screens to prevent objects from being inserted into the cooler. Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ANSI 61 and NSF/ANSI 372.



	PGVD8ACSL	PGVDACSL
Features:	• Universal design: high right or high left • Built-in 100 micron strainer stops particles before they enter the waterway • Waterways are Lead-Free in materials & construction • Vandal resistant water saver bubbler • Vandal resistant mechanical front push button • One-piece vandal resistant bubbler keyed into position • Vandal resistant fasteners • Galvanized steel louver and bottom screens • Stainless steel top and heavy duty galvanized steel frame • Stream height adjustment • Includes integral self-scouring waste drain • High efficiency cooling system • Rated for Indoor and Outdoor	
Filtration:	Option to add filtration	
Power:	115 Volts, 60 Hz	
Activation By:	Manual Activation on Fountain	
Mounting Type:	Wall Mounted	
Chilling Option:	8.0 gph*	Non-Refrigerated
Full Load Amps:	5.5 amps	0 amps
Rated Watts:	550	0
Approx. Net Weight:	70lbs	40 lbs
Installation Location:	Indoor/Outdoor	

When used or stored in non-temperature controlled environments, the unit must be adequately winterized and/or protected from extreme heat to prevent damage.

Installation

- Prior to rough-in consult with local, state and federal codes for proper mounting height
- Shipped with complete instructions and wall mounting bracket
- Removable side and front panels provide easy access for installation

Finishes

- Standard cabinet finish: Stainless steel

Options

- OASIS Versafilter III Kit 041253-001**

Limited 5-Year Warranty

(Continental limits of the United States and Canada)

Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed



WARNING:
Cancer and Reproductive Harm
www.P65Warnings.ca.gov



*Industry standard rating condition at 90°F ambient, 80°F inlet water and 50°F drinking water temperature

Specifications subject to change without notice
**Filters are not rated for outdoor use

OUTDOOR RATED VANDAL RESISTANT UNIVERSAL BARRIER-FREE VERSACOOLER® II

