

Woven



Colors



White
VTL WOWH



Beige
VTL WOBE



Brown
VTL WOBR




Gray
VTL WOGR



Black
VTL WOBL

Sizes



12" x 24" x 9mm
Rectified

W O V E N

Field Tiles*

SIZE	ACTUAL	THICKNESS	FINISH
12" x 24" Rectified	11.81" x 23.62"	9.00mm	Matte/Natural
* Not all sizes/trims are available in all colors and finishes, scan QR code for product details.			

Mosaics & Coordinating Trims*

SIZE	ACTUAL	FINISH
2" x 2" Mosaic	11.73" x 11.73"	Matte/Natural
1" x 6" Straight Stacked Mosaic Mosaic	11.81" x 23.62"	Matte/Natural
3" x 24" Bullnose Rectified	2.78" x 23.62"	Matte/Natural
Recommended Grout Joint: 1/8" - Rectified 3/16" - Non Rectified		

Product Characteristics

	MATTE/NATURAL
Breaking Strength (ASTM C648 or ISO 10545-4)	≥2600N
Chemical Resistance (ASTM C650 or ISO 10545-13)	N/A
DCOF	≥0.42
Deep Scratch Resistance - Unglazed (ISO 10545-6)	N/A
Frost Resistance (ASTM C1026 or ISO 10545-12)	Resistant
Mohs Hardness - EN101	N/A
Water Absorption (ASTM C373 or ISO 10545-3)	N/A
Certifications	N/A
Country of Origin	Malaysia
Shade Variation Code	V1

Application**

		WALL	FLOOR
Interior	Residential	•	•
Interior	Commercial	•	•
Interior	Heavy Commercial	•	•
Exterior	Residential/Commercial		

** These recommendations are not defined by ANSI Standards

Material

Glazed Color-Body Porcelain



V1 Uniform Appearance



Made in Malaysia



Frost Resistant



Scan QR Code for
Product Information and
Installation Images

Request samples.

www.vitlsurfaces.com
samples@vitlsurfaces.com



VITL
SURFACES
COMMERCIAL