

**HUBBELL**  
Wiring Device-Kellems

**Locking Devices, Twist-Lock®,  
Industrial, Male Plug, 20A 125V, 2-  
Pole 3-Wire Grounding, L5-20P,  
Screw Terminal, Black and White**

By Hubbell Wiring Device-Kellems  
Catalog # [HBL2311](#)

Locking Devices, Twist-Lock®, Industrial, Male Insulgrip® Plug,  
20A 125V AC, 2-Pole 3-Wire Grounding, NEMA L5-20P, Screw  
Terminal, Black and White Nylon.



## General

Application	
Catalog Number	HBL2311
Color	
Cord Range	0.360"-0.930" (9-24)
EU RoHS Indicator	Yes
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Horsepower - Maximum	1
Item Type	20A Male Insulgrip® Plug
Material	Nylon
Material - Mounting Hardware	Cord Mounted
Number Of Poles	2-Pole
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Performance	Electrical - Current Interrupting - Certified for current interrupting at full rated current
	Electrical - Dielectric Voltage - Withstands 2,000V minimum
	Environmental - Flammability - HB or better per UL94 or CSA 22.2 No. 0.6
	Environmental - Moisture Resistance - IP20 Suitability
	Environmental - Operating Temperatures - Maximum Continuous 75°C Minimum -40°C (w/o impact)
	Mechanical - Terminal Accommodation - #16 AWG - #8 AWG stranded copper wire only.
	Mechanical - Terminal Identification - Terminals identified in accordance with UL 498
Type	Plugs
	Plugs
UPC	783585037707

## Dimensions

Dimensions	2.26 in x 2.26 in x 2.75 in
Display Size	Standard Sized
Height	2.75 in
Length	2.26 in
Weight	0.25 lb
Width	2.26 in

## Electrical Ratings

Amperage Rating	20 A
Connectivity	Pressure Terminal Screws
Current / Amperage Rating	20 A
Current Rating	20 A
Dielectric Strength	Withstands 2,000V minimum
Phase	Single Phase
Voltage Rating	125 VAC
Voltage Rating Description	125 VAC

## Conductor Related

Cable Range	0.360 - 0.930 in
Cord Type	All Listed Portables
Number Of Wires	3-Wire
Wire Size	#16 AWG to #8 AWG

## Certifications And Compliance

Industry Standard(s)	Certified to CSA C22.2 No.42
	Fed.Spec. W-C-596
	Listed to UL 498
Nema Rating	L5-20P
Standards - RoHS Compliance Status	CM

## Logistics

Carton Quantity	30
Pallet Quantity	3060

## Product Assets

[Catalogs - WDK Catalog Full 2024](#)  
[Warranty - Industrial & Commercial Products](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved  
WDK\_MX-HBL2311-SPEC-EN | REV 6/2024