

# Omnitron Optical Transceivers

## SFP Optical Transceivers


Omnitron Small Form Pluggable (SFP) Optical Transceivers are interchangeable, compact media connectors. They enable a single network device to connect to a wide variety of fiber and copper cable types and distances.

SFP Optical Transceivers are used to customize iConverter®, FlexPoint™, OmniConverter®, RuggedNet®, miConverter™ and most 3rd party products to meet specific networking protocols and media requirements. They support multimode dual fiber, single-mode dual fiber, single-mode single-fiber, Coarse Wave Division Multiplexing (see the CWDM Optical Transceiver Data Sheet) and Unshielded Twisted Pair copper cabling.

SFP Optical Transceivers reduce network equipment inventories by eliminating the need to maintain surplus modules of various media types for network repairs or upgrades. They also enable network upgrades and growth by providing interchangeable fiber and copper connectors that can easily adapt to and modify any existing network.

Based on the MSA SFF-8472 and INF-8077i standards, Omnitron Optical Transceivers support digital diagnostic capabilities, providing enhanced diagnostic information to assist network administrators with network maintenance. When used in iConverter modules managed by SNMP management software, such as NetOutlook®, Omnitron Optical Transceivers can collect enhanced, real time transceiver diagnostic information including fiber optic TX and RX power, voltage and transceiver temperature.

By providing compact physical size and the ease of interchangeability, Omnitron Optical Transceivers provide a cost-effective and flexible solution for network designs.



## KEY FEATURES

- Omnitron SFP Optical Transceivers enable flexible fiber and copper connectivity
- Compatible with iConverter media converter modules, T1/E1 Multiplexers and Network Interface Devices that support SFP transceivers
- Compatible with FlexPoint, OmniConverter, RuggedNet and miConverter media converter modules that support SFP transceivers
- Compliant with IEEE 802.3u Fast Ethernet and 802.3z Gigabit Ethernet specifications
- Supports operational data rates for SONET OC-3/12/48, SDH STM-1/4/16, and Fiber Channel x1/x2
- Compliant with MSA SFF-8472 and INF-8077i standard, which provides interoperability with other network devices
- Compliant with RoHS (6/6), WEEE and REACH
- Supports a wide variety of cable types
- Supports Digital Diagnostic capability
- Low EMI metal enclosure
- Commercial (0° C to +50° C) and Industrial (-40° C to +85° C) temperature ranges available
- One (1) Year Warranty and free 24/7 Technical Support

## ORDERING INFORMATION

### Fiber SFPs supporting Fast Ethernet, SONET OC-3 and SDH STM-1 network protocols.

| Model  | Fiber Type | Spec. Distance (km) | Wavelength (nm) | Min. Tx Power (dBm) | Max. Tx Power (dBm) | Min. Rx Power (dBm) | Max. Rx Power (dBm) | Min. Attenuation (dB) | Link Budget (dB) |
|--------|------------|---------------------|-----------------|---------------------|---------------------|---------------------|---------------------|-----------------------|------------------|
| 7006-0 | MM/DF      | 5                   | 1310            | -20                 | -14                 | -31                 | -14                 | -                     | 11               |
| 7007-1 | SM/DF      | 30                  | 1310            | -15                 | -8                  | -32                 | -8                  | -                     | 17               |
| 7007-2 | SM/DF      | 60                  | 1310            | -5                  | 0                   | -35                 | -3                  | 3                     | 30               |
| 7007-3 | SM/DF      | 120                 | 1550            | -5                  | 0                   | -35                 | -3                  | 3                     | 30               |
| 7014-0 | MM/SF      | 5                   | 1310 / 1550     | -15                 | 0                   | -28                 | -3                  | 3                     | 13               |
| 7015-0 | MM/SF      | 5                   | 1550 / 1310     | -15                 | 0                   | -28                 | -3                  | 3                     | 13               |
| 7014-1 | SM/SF      | 30                  | 1310 / 1550     | -14                 | -8                  | -32                 | -3                  | -                     | 18               |
| 7015-1 | SM/SF      | 30                  | 1550 / 1310     | -14                 | -8                  | -32                 | -3                  | -                     | 18               |
| 7014-2 | SM/SF      | 50                  | 1310 / 1550     | -8                  | 0                   | -34                 | -3                  | 3                     | 26               |
| 7015-2 | SM/SF      | 50                  | 1550 / 1310     | -8                  | 0                   | -34                 | -3                  | 3                     | 26               |
| 7014-3 | SM/SF      | 80                  | 1310 / 1550     | 0                   | 5                   | -34                 | -3                  | 8                     | 34               |
| 7015-3 | SM/SF      | 80                  | 1550 / 1310     | 0                   | 5                   | -34                 | -3                  | 8                     | 34               |

Contact Omnitron for other configurations and industrial temperature (-40° C to +85° C) models.

### Fiber SFPs supporting Gigabit Ethernet, 1G Fiber Channel, SONET OC-12 and SDH STM-4 network protocols.

| Model  | Fiber Type | Spec. Distance (km) | Wavelength (nm) | Min. Tx Power (dBm) | Max. Tx Power (dBm) | Min. Rx Power (dBm) | Max. Rx Power (dBm) | Min. Attenuation (dB) | Link Budget (dB) |
|--------|------------|---------------------|-----------------|---------------------|---------------------|---------------------|---------------------|-----------------------|------------------|
| 7206-0 | MM/DF      | 0.22 / 0.55         | 850             | -9.5                | -4                  | -17                 | -3                  | -                     | 7.5              |
| 7206-6 | MM/DF      | 2                   | 1310            | -9.5                | -3                  | -19.5               | -3                  | -                     | 10               |
| 7207-1 | SM/DF      | 12                  | 1310            | -9.5                | -3                  | -21                 | -3                  | -                     | 11.5             |
| 7207-2 | SM/DF      | 34                  | 1310            | -5                  | 0                   | -24                 | -3                  | 3                     | 19               |
| 7207-3 | SM/DF      | 80                  | 1550            | -4                  | 1                   | -24                 | -3                  | 4                     | 20               |
| 7207-4 | SM/DF      | 110                 | 1550            | 0                   | 5                   | -24                 | -3                  | 8                     | 24               |
| 7207-5 | SM/DF      | 140                 | 1550            | 2                   | 5                   | -30                 | -8                  | 13                    | 32               |
| 7207-6 | SM/DF      | 160                 | 1550            | 1                   | 5                   | -33                 | -8                  | 13                    | 34               |
| 7214-0 | MM/SF      | 0.55                | 1310 / 1550     | -9                  | -3                  | -18                 | -3                  | -                     | 9                |
| 7215-0 | MM/SF      | 0.55                | 1550 / 1310     | -9                  | -3                  | -18                 | -3                  | -                     | 9                |
| 7214-1 | SM/SF      | 20                  | 1310 / 1550     | -9                  | -3                  | -21                 | -3                  | -                     | 12               |
| 7215-1 | SM/SF      | 20                  | 1550 / 1310     | -9                  | -3                  | -21                 | -3                  | -                     | 12               |
| 7214-2 | SM/SF      | 40                  | 1310 / 1550     | -3                  | 2                   | -23                 | -3                  | 5                     | 20               |
| 7215-2 | SM/SF      | 40                  | 1550 / 1310     | -3                  | 2                   | -23                 | -3                  | 5                     | 20               |
| 7214-3 | SM/SF      | 60                  | 1310 / 1550     | 0                   | 5                   | -24                 | -1                  | 6                     | 24               |
| 7215-3 | SM/SF      | 60                  | 1550 / 1310     | -2                  | 4                   | -25                 | -1                  | 5                     | 23               |
| 7216-1 | SM/SF      | 20                  | 1310 / 1490     | -9                  | -3                  | -21                 | -3                  | -                     | 12               |
| 7217-1 | SM/SF      | 20                  | 1490 / 1310     | -9                  | -3                  | -21                 | -3                  | -                     | 12               |
| 7216-2 | SM/SF      | 40                  | 1310 / 1490     | -3                  | 0                   | -20                 | -3                  | 3                     | 17               |
| 7217-2 | SM/SF      | 40                  | 1490 / 1310     | -3                  | 0                   | -20                 | -3                  | 3                     | 17               |
| 7218-4 | SM/SF      | 80                  | 1510 / 1570     | -4                  | 1                   | -26                 | 0                   | 1                     | 22               |
| 7219-4 | SM/SF      | 80                  | 1570 / 1510     | -4                  | 1                   | -26                 | 0                   | 1                     | 22               |

Contact Omnitron for other configurations and industrial temperature (-40° C to +85° C) models.

## ORDERING INFORMATION

### Copper SFPs for Gigabit Ethernet

| Model      | Data Rate       | Distance |
|------------|-----------------|----------|
| 7299-RJ    | 1000Mbps        | 100m     |
| 7299-RJ-GI | 10/100/1000Mbps | 100m     |

Contact Omnitron for other configurations and industrial temperature (-40° C to +85° C) models.

### Fiber SFPs for devices that support 2G Fiber Channel, SONET OC-48 and STM-16 network protocols.

| Model  | Fiber Type | Spec. Distance (km) | Wavelength (nm) | Min. Tx Power (dBm) | Max. Tx Power (dBm) | Min. Rx Power (dBm) | Max. Rx Power (dBm) | Min. Attenuation (dB) | Link Budget (dB) |
|--------|------------|---------------------|-----------------|---------------------|---------------------|---------------------|---------------------|-----------------------|------------------|
| 7226-0 | MM/DF      | 0.30                | 850             | -9                  | -3                  | -17                 | 0                   | -                     | 8                |
| 7227-1 | SM/DF      | 15                  | 1310            | -10                 | -3                  | -18                 | -3                  | -                     | 8                |
| 7227-2 | SM/DF      | 40                  | 1310            | -2                  | 3                   | -27                 | -9                  | 12                    | 25               |
| 7227-3 | SM/DF      | 80                  | 1550            | -2                  | 4                   | -20                 | 0                   | 4                     | 18               |

Contact Omnitron for other configurations and industrial temperature (-40° C to +85° C) models.

### Fiber SFPs for devices that support 8G Fiber Channel.

| Model  | Fiber Type | Spec. Distance (km) | Wavelength (nm) | Min. Tx Power (dBm) | Max. Tx Power (dBm) | Min. Rx Power (dBm) | Max. Rx Power (dBm) | Min. Attenuation (dB) | Link Budget (dB) |
|--------|------------|---------------------|-----------------|---------------------|---------------------|---------------------|---------------------|-----------------------|------------------|
| 7287-1 | MSM/DF     | 10                  | 1310            | -8                  | 0                   | -16                 | 0.5                 | -                     | 8                |

Contact Omnitron for other configurations and industrial temperature (-40° C to +85° C) models.

©2020 Omnitron Systems Technology, Inc. All rights reserved. iConverter, NetOutlook, OmniConverter and RuggedNet are registered trademarks of Omnitron Systems Technology, Inc. FlexPoint and miConverter are trademarks of Omnitron Systems Technology, Inc. Trademarks are owned by their respective companies. Specifications subject to change without notice.

