

PLASTIC DRUM STANDARD PRODUCT DESCRIPTION

		Product Name: GP-55FR	
Regulatory Information: un 1H1/Y1.9/150 (Test Report P106) un 1H1/Y1.4/150 with vent (Test Report P107) un 1H1/Y1.4/150 w/vent (Test Report P159, #7)		Bill of Materials: Body: GP-55FR, extrusion blow molded high molecular weight high density polyethylene (HMW-HDPE) Fittings: 2" BTR and 2" NPS. Double Buttress configuration available. 56X4 European BTR available. Vented bungs are available as an option. (BTR = Buttress, NPS = National Pipe Straight thread)	
		Product Illustration: 	
Nominal Capacity: 55.0 U.S. Gallons	Outage: 2.7 U.S. Gallons	Overall Height: 34.9 inches	Total Weight: 23.8 lbs.
Maximum Capacity: 57.7 U.S. Gallons	Outage %: 4.9 %	Body Height: N/A inches	Body Weight: 23.6 lbs.
Export Cubes: 10.41 cu. ft.	Nominal O.D.: 23.4 inches	Mid Panel Height: 10.1 inches	Min. Wall Thickness: 0.090 inches
Special Notes: 1) Maximum filling temperature 150 F for all foods and other FDA regulated substances. 160 F for all non-foods and other substances that are not regulated by FDA. When filled at these recommended maximum filling temperatures drums should be allowed to cool to ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum which can compromise stacking capability. 2) Drums may be stacked 3 high (1+2) maximum with pallets between drums. For nonvented drums, maximum top load on bottom drums not to exceed 2000 lbs each. For vented drums, maximum top load on bottom drums not to exceed 1400 lbs each. Pallets should be of good quality that provides adequate support for plastic drums. 3) Handle with parrotbeak, side grabber, and sling. 4) Fits four wide in standard trailer. 5) Recycle symbol embossed on bottom. 6) Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler. 7) UN approval valid for Lavonia only.			

DISCLAIMER

This specification does not relieve the customer of their ultimate responsibility for the determination of the appropriate container. It is the customer's responsibility to select the appropriate packaging based upon all information at their disposal including the specific application, regulatory compliance, product compatibility and shipping requirements. WE HEREBY DISCLAIM AND EXCLUDE ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

DISTRIBUTED BY:



REF NO.:

DWG31922

DESCRIPTION:

55 Gallon HDPE TH Drum, (2) 2" Fittings,
Top & Bottom Chimes, Y1.9/150