



Structured Cable Products™

Quality Installations Deserve Quality Products

www.scpcat5e.com
 sales@scpcat5e.com
 Direct: 954-327-5770
 Toll Free: 866-470-5742

SCP PART#: 18/2FPLR-500-BOX

UPC: 810070010669

DESCRIPTION:

Unsh Riser FPLR 2/C 18/1 AWG SBC, PVC Insulation, Red PVC Riser Jacket, 500 FEET/152M

General Specification of Product :

Final Diameter : 0.151 inches 3.835 mm

Total Cable Weight: 28 kg/km 19 lbs/1000 ft

Conductor : 18 AWG Solid Bare Copper

Insulation : PVC

Outer Jacket : PVC

Print Notes : Sequentially marked per 2FT (0 - infinity)

Standard Print : STRUCTURED CABLE PRODUCTS - - - P/N 18/2FPLR - - - RISER FIRE ALARM CABLE (UL) CL2R/CL3R E198137-SCP OR FPLR (UL) C(UL) CMG CMR UNSH 2/C 18 AWG SOLID PVC JKT --- ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 RoHS

Electrical Characteristics :

DC Resistance 25°C: 6.6 Ohms / 1000 ft

Mutual Capacitance : 22.6 pF/ft

Impedance : 80 Ohms

Velocity of Prop : 64 %

Inductance. : 1.4 mH/km

Additional Information :

Cabled OD Avg: 0.104
 Ins Thickness: 0.010
 Jkt Thickness: 0.015
 Certified: UL CL2R/CL3R OR FPLR UL C(UL) CMG/CMR
 Flame Rating: Riser
 Max Voltage: 300V
 Packaging: Reelex Box 11.5 x 11.5 x 7.75"
 Packaged Weight: 19 lbs / 10 kgs

(All of the above values are approximated to within +/- 10%)

QMS Registered ISO 9001

2981802.03R.500