



Steel - Raintight

Images



Application

For maintaining wet locations seal on rated enclosures. Coated Washer installs on outside of 3R rated enclosure. Uncoated washer should be installed inside to maintain raceway continuity. Center reducing washers in middle of knock-out. Listed for use with Wet Location Connectors. Patent Pending

Product Information

Material: Galvanized Steel with EPDM Rubber Coating

Certifications & Codes:

Federal Specification Number: A-A-50553

NEMA Standard: FB-1

UL File Number: E11259, cULus

UL Standard: UL514B

UNSPSC: 39121321

Catalog ID: 1063-RT

UPC Number: 78174714063

Description: Mighty-Seal® 1" to 3/4" Raintight Reducing Washers. Product contains one coated and one uncoated galvanized steel reducing washer. Maintains Raceway Integrity. Sunlight Resistant. Suitable for Wet Locations.

Application: For maintaining wet locations seal on rated enclosures. Coated Washer installs on outside of 3R rated enclosure. Uncoated washer should be installed inside to maintain raceway continuity. Center reducing washers in middle of knock-out. Listed for use with Wet Location Connectors. Patent Pending

Trade Size: 1" - 3/4"

Country of Manufacture: USA

Std Pkg Qty: 200

Unit Qty: 20

[Download Photo Image](#)

[Download Dimensional Image](#)

Dimension A in Inches: 1.05

Dimension B in Inches: 1.84

Dimension C in Inches: 1.38