

Project: Type: Prepared By: Date:



#### **Features and Benefits**

Energy efficient replacement for incandescent and halogen reflector lamps

Constructed from durable plastic which lowers risk of breakage

Rated for use in enclosed and open fixtures in dry or damp locations

Frosted lens produces smooth diffuse light

 $Longer\,life span\,compared\,to\,legacy\,equivalents\,minimizes\,replacement\,and\,maintenance\,costs$ 

**ENERGY STAR Compliant** 

Dimmable with common dimmer types (see Dimmer Compatibility List)

Performance	Beam Angle:	Housing Finish:	
Product Type:	110°	White	
Reflector			
	Electrical	Lens Finish:	
Input Wattage:	Power Factor:	Frosted	
7.5W	>0.7		
		Installation	
Lumens:	Dimmable:	Base Type:	
650lm	Yes, down to 20%	E26 Edison	
Efficacy:	Input Voltage:	Other	
87lm/W	120V	Technology EQ:	
		Incandescent	
L70 Lifespan:	Operating Frequency:		
25,000-Hour LED lifespan based on IES LM-70 results	60 Hz	Warranty (Years):	
		3 years	
Wattage Equivalency:	Operating Temperature:		
55	-20°C to 45°C	Compliance	
IFD Characteristics	Construction	UL Listed:	
LED Characteristics	Construction	Yes	
Color Accuracy (CRI):	Bulb Shape:		
80	BR30	Environment:	
6.1 T		Damp / Enclosed	
Color Temperature:	Enclosure Material:		
3000K	Plastic	Energy Star ID:	
		2356090	



# **Technical Specifications (continued)**

Rohs:

Mercury and UV free. RoHS-compliant components.

FCC:

Complies with Part 15B of the FCC Rules

### **Certification Model Number:**

R10045(BR30-7.5-830-DIM)

## **Minimum Compartment Size**

Length x Width x Height [in]	Lamp Quantity	
11	1	

### **Case and Pallet Dimensions**

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	6	0	0	0
PALLET	1056	0	0	0

