
Starling




Colors







Dolomite
VTL SRDO


Sizes



24" x 48" x 8mm
Rectified




24" x 24" x 8mm
Rectified




12" x 24" x 8mm
Rectified



3" x 12" x 8mm
Rectified



11" x 12" x 8mm
Rectified



12" x 15" x 8mm
Rectified

STARLING

Field Tiles*

SIZE	ACTUAL	THICKNESS	FINISH
24” x 48” Rectified	24.00” x 48.00”	8.00mm	Polished
24” x 48” Rectified	24.00” x 48.00”	8.00mm	Matte
24” x 24” Rectified	24.00” x 24.00”	8.00mm	Polished
24” x 24” Rectified	24.00” x 24.00”	8.00mm	Matte
12” x 24” Rectified	12.00” x 24.00”	8.00mm	Polished
12” x 24” rectified	12.00” x 24.00”	8.00mm	Matte
3” x 12” Rectified	3.00” x 12.00”	8.00mm	Polished
3” x 12” Rectified	3.00” x 12.00”	8.00mm	Matte

* Not all sizes/trims are available in all colors and finishes, scan QR code for product details.

Mosaics & Coordinating Trims*

SIZE	ACTUAL	FINISH
12” x 15” Herringbone Mosaic Rectified	12.00” x 15.00”	Polished
12” x 15” Herringbone Mosaic Rectified	12.00” x 15.00”	Matte
11” x 12” Hexagon Mosaic Rectified	11.00” x 12.00”	Polished
11” x 12” Hexagon Mosaic Rectified	11.00” x 12.00”	Matte
3” x 24” Bullnose Rectified	3.00” x 24.00”	Polished
3” x 24” Bullnose Rectified	3.00” x 24.00”	Matte
6” x 12” Cove Base Rectified	6.00” x 12.00”	Matte

Recommended Grout Joint: 1/8” - Rectified
3/16” - Non Rectified

Product Characteristics

	POLISHED
Breaking Strength (ASTM C648 or ISO 10545-4)	≥400 lb/ft2
Chemical Resistance (ASTM C650 or ISO 10545-13)	Resistant
DCOF	≥0.42
Deep Scratch Resistance - Unglazed (ISO 10545-6)	N/A
Frost Resistance (ASTM C1026 or ISO 10545-12)	Resistant
Mohs Hardness - EN101	≥ 7
Water Absorption (ASTM C373 or ISO 10545-3)	≤0.4%
Certifications	Greenguard, Bureau Veritas NSF, EPD
Country of Origin	USA
Shade Variation Code	V3

Application**

		WALL	FLOOR
Interior	Residential	•	•
Interior	Commercial	•	•
Interior	Heavy Commercial	•	
Exterior	Residential/Commercial	•	

** These recommendations are not defined by ANSI Standards

Material

Glazed Color-Body Porcelain

V3 Moderate Variation

Made in USA

Frost Resistant

Recommend an offset pattern ≤33%

DCOF: ≥0.42

Water Absorption: ≤0.4%

Must be Sealed

Greenguard, Bureau Veritas NSF, EPD

PEI Rating 4

Scan QR Code for Product Information and Installation Images

Request samples.

www.vitlsurfaces.com
samples@vitlsurfaces.com

VITL SURFACES COMMERCIAL