Two Hole, Slotted, Long Barrel, Compression Lugs



Listed 486





Part No.	Conductor Size (AWG)	Hole Spacing Range	Hardware Size	Inspection Port	Color Codes	Box Qty.	Approx. Box Wt. (lbs.)
GECLB62BC	6	.75″ to 1″	3/8″	Yes	Blue	50	2
GECLB62BC250BK	6	.75″ to 1″	3/8″	Yes	Blue	250	10
GECLB62BCNP	6	.75″ to 1″	3/8″	No	Blue	50	2
GECLB62BCNP250BK	6	.75″ to 1″	3/8″	No	Blue	250	10
GECLB22BCS	2 Sol.	.75″ to 1″	3/8″	Yes	White	50	2
GECLB22BCS250BK	2 Sol.	.75″ to 1″	3/8″	Yes	White	250	15
GECLB22BCSNP	2 Sol.	.75″ to 1″	3/8″	No	White	25	2
GECLB22BCSNP250BK	2 Sol.	.75″ to 1″	3/8″	No	White	250	14
GECLB22BC	2	.75″ to 1″	3/8″	Yes	Brown	50	3
GECLB22BC250BK	2	.75″ to 1″	3/8″	Yes	Brown	250	15
GECLB22BCNP	2	.75″ to 1″	3/8″	No	Brown	25	2
GECLB22BCNP250BK	2	.75″ to 1″	3/8″	No	Brown	250	16

- Manufactured from electro plated tinned copper.
- For use on copper or tinned copper conductors.
- 250 pack comes in one gallon bucket.

Long Barrel Butt Splices

Part No.	Conductor Size (AWG)	Box Qty.	Approx. Box Wt. (lbs.)
CLBBS8	8	50	1
CLBBS6	6	50	1
CLBBS4	4	50	2
CLBB2S	2 Sol.	50	4
CLBBS2	2	50	4
CLBBS2/0	2/0	10	2
CLBBS4/0	4/0	10	2
CLBBS250	250	10	3
CLBBS500	500	10	5



Listed 486