

TN-GLC-ZX-SM Series

Cisco Compatible Gigabit SFP Modules

1000Base-LX Single Mode (LC) With DMI



TN-GLC-ZX-SM-RGD

Features

- Extended operating temperature
-40°C to +85°C (TN-GLC-ZX-SM-RGD
Module Only)

Specifications

Standards	IEEE 802.3
Dimensions	Width: 0.52" [13 mm] Depth: 2.18" [55 mm] Height: 0.33" [8 mm]
Power Consumption	0.66 Watts
Power Input	3.3V
Environment	Operating: 0°C to 70°C Storage: -40°C to 85°C TN-GLC-ZX-SM-RGD Operating: -40°C to 85°C Storage: -40°C to 100°C
Compliance	IEC-60825, FDA 21, CFR 1040.10 and 1040.11
Warranty	Lifetime

Ordering Information

Duplex

- TN-GLC-ZX-SM**
1000Base-LX 1550nm single mode (LC) with
DMI [80 km/49.7 mi.] Link Budget: 24.0 dB
- TN-GLC-ZX-SM-12**
1000Base-LX 1550nm single mode (LC) with
DMI [120 km/74.6 mi.] Link Budget: 31.0 dB
- TN-GLC-ZX-SM-15**
1000Base-LX 1550nm single mode (LC) with
DMI [150 km/93.2 mi.] Link Budget: 37.0 dB
- Extended Operating Temperature**
-40°C to +85°C
- TN-GLC-ZX-SM-RGD**
1000Base-LX 1550nm single mode (LC) with
DMI [80 km/49.7 mi.] Link Budget: 24.0 dB

Note: The Transition Networks TN-GLC-ZX-SM series small form factor pluggable (SFP) transceiver modules are designed to install in any SFP port allowing for 1000Base-LX interfaces to the network through the SFP connector. The TN-GLC-ZX-SM transceivers are Cisco Compliant* and are designed for bi-directional serial-optical data communication such as Gigabit Ethernet or fiber channel at speeds up to 1.25 Gbps.

*Transition Networks' SFP modules fully comply with the Multi-Sourcing Agreement (MSA). This compliance allows our SFP modules to be used in all other MSA compliant SFP platforms. In addition, Transition Networks SFP modules are also Compliant with all Cisco SFP-based routers and switches, as well as Cisco's IOS software. Transition Networks SFP modules ARE NOT Cisco OEM brand modules.