

## Ceiling Flush Mount

77063, 77064, 77065, 77263, 77264, 77265 | 1.4

# VISUAL COMFORT & Co.

GENERATION LIGHTING

### SAVE THESE INSTRUCTIONS!

#### GENERAL PRODUCT INFORMATION:

These fixtures are intended to be installed utilizing NEC compliant junction boxes.

This product is safety listed for damp locations.


Incandescent version may be dimmed with a standard incandescent dimmer. LED version may be dimmed with a LED dimmer. Consult lamp manufacturer for additional information.

This instruction shows a typical installation.


#### CAUTION - RISK OF FIRE

This product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.

Use minimum 90°c supply conductors.



# Install the Fixture



- 1** Secure the mounting plate to the electrical box with two mounting plate screws.
- 2** Connect the fixture to a suitable ground in accordance to local electrical codes.
- 3** Connect the white fixture wire to the neutral power line wire with a wire nut.
- 4** Connect the black fixture wire to the hot power line wire with a wire nut.
- 5** Align the key slots on the fixture base to the mounting plate screws, place the fixture base onto the mounting plate, and secure it by rotating it to the narrow portion of the keyed slot.
- 6** Screw the threaded nipple to the bottom of the fixture base.
- 7** Screw the lamp(s) into the socket(s). Refer to the label on the socket for Max Wattage Information.
- 8** Slip the shade through the threaded nipple and secure it in place by fastening it with the flat washer and hex nut.
- 9** Install the decorative cup to the bottom of the shade and secure it by tightening the finial.