

DEF-GUARD™

NRR 23 Passive Earmuff



Dielectric Design

Provides non-conductive protection in hazardous electrical environments

Ultra Lightweight

Weighs less than 5 oz for all day wear

Adjustable Headband

Adjustable headband provides a comfortable, custom fit

Foam Filled Ear Cushions

Soft, foam filled ear cushions provide a comfortable seal



TECHNICAL DATA

| FOLDS | No |
|-------------------|-------------------------|
| ADJUSTABLE | Yes |
| EARMUFF STYLE | Passive |
| COLOR | Red Earcup / Black Band |
| CASE QUANTITY | 40 |
| COUNTRY OF ORIGIN | CHINA |

PERFORMANCE DATA

| NKK | 23 |
|-------------|----------------------|
| STANDARDS | ANSI/ISEA S3.19-1974 |
| | CSA Z94.2-14 CLASS A |
| | |
| PART NUMBER | DF0310HC |
| | |

NRR 23 PASSIVE

APPLICATION DATA

| Construction | Manufacturing |
|--------------|---------------|
| Landscaping | Aviation |
| Mining | |

ATTENUATION DATA

DESCRIPTION

| FREQUENCY (HZ) | 125 | 250 | 500 | 1000 | 2000 | 3150 | 4000 | 6300 | 8000 |
|-------------------------|-----|------|------|------|------|------|------|------|------|
| MEAN ATTENUATION (dB) | 16 | 21.4 | 28.4 | 35.4 | 38.2 | 39.0 | 35.3 | 35.5 | 36.9 |
| STANDARD DEVIATION (dB) | 4.1 | 3.6 | 3.3 | 3.2 | 3.3 | 3.0 | 3.1 | 3.5 | 3.9 |

Tested according to ANSI/ISEA S3.19-1974 standards



work hard. stay safe.

DEFw-SSH_Rev03