



STAINLESS STEEL SINK BUBBLER MODEL 041768-001

Suggested Specification

Easily add safe, accessible drinking water to any classroom sink with the stainless steel sink bubbler – a durable, chrome-finished solution designed for everyday use in educational environments.

Features:	•	Anti-Microbial Flexible Mouth Guard
	•	Adjustable Stream Flat Head Screw
	•	Stainless Steel Mounting Kit With Two Screws
	•	Easy to install deck-mount 1/2-14 NPS Male Thread connection
	•	Manually activated handle to dispense water
Finish:	•	Chrome
Dimensions:	7.92 x 6 x 2 inches	
Approx. Net Weight	2.72 lbs	
Installation Location:	Indoor	



Ships in one box.

Installation Steps

- Prior to rough-in consult with local, state and federal codes for proper mounting height
- Tools required to install includes a Philips screwdriver, plumbers putty, teflon tape and a rag.
- First apply a thin uniform layer of plumber's putty to the underside of the faucet. Place faucet shank through the mounting hole. Locate the two screws for the mounting nut. insert and thread screws only until flush with the mounting nut. From underneath the sink, slide the rubber washer and steel plate onto the faucet shank. Thread and hand tighten the mounting nut then tighten the two screws to secure.
- Next Connect water supply line to the faucet shank.
- The self-close basin faucet was preset at 60 PSI to shut off water, different water pressure might affect the faucet and cause it not to function properly. if need be, remove the handle cap, sleeve and Celcon Samson nut.
- Lastly, use wrench to adjust brass square nut, turn counter-clockwise to tighten the cartridge and turn it clockwise to loosen the cartridge until the faucet functions properly then proceed to tighten the cartridge 90 degrees more before reassembling the Celcon Samson nut, sleeve, and handle cap back in place.

MODEL: _____ QTY: _____

PROJECT: _____

CONTACT: _____

NOTES: _____

APPROVAL: _____ DATE: _____

Specifications subject to change without notice



STAINLESS STEEL SINK BUBBLER
MODEL 041768-001

