

Lightology

lightology.com
866-954-4489
05-18-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **WAC1362371**
 Approved On: _____ Approved By: _____

FQ 2 inch Square Downlight with Trim By WAC Lighting



Description

The FQ 2 Inch Square With Trim Downlight Trim is designed for use with FQ 2 Inch Series of recessed housings by WAC Lighting. This high performance LED luminaire will provide quality lighting in both commercial and residential settings. Features glare control with 30 degree shielding, 35 degree vertical tilting and 360 degree horizontal rotation. Ceiling cutout: 3.5 inch. Accommodates 0.5 to 1 inch ceiling thickness. Dimmable with TRIAC and ELV at 120V, and 0-10V at 277V. Note 1: Field changeable beam angle with reflectors provided (25 degree, 40 degree, 55 degree). Lumens shown are based on 40 degree beam angle. Note 2: A complete fixture requires the trim and a housing, sold separately.

Specifications

COLOR	N/A
BODY FINISH	White
WATTAGE	N/A
DIMMER	Low Voltage Electronic
DIMENSIONS	4"W x 4.75"H
INTEGRATED LED MODULE	1x LED/120-277V LED

Technical Information

APERTURE SHAPE	Square
CEILING TYPE	Drywall with Trim
FUNCTION	Downlight
LAMP LIFE	90 hours
BEAM ANGLE	40°
COLOR RENDERING	.90 CRI
LAMP COLOR	.2700K
LUMINOUS FLUX	.1850 lumens



Shown in white

Model	Beam	lumens	CRCP	Color Temp	CRI	Finish	Reflector/Trim
FQ2501 Square Trim	W 25°	1850	4515	927	2700K	90	Black Dark Bronze Alpine White White
	F 40°	1850	3115				
	W 55°	1850	2400				
FQ2502 Square Trim	W 25°	1860	5005	930	3000K	90	BK DB HWHT WT
	F 40°	1860	3275				
	W 55°	1860	2525				
FQ2503 Square Trim	W 25°	2030	5105	935	3000K	90	BK DB HWHT WT
	F 40°	1990	3345				
	W 55°	1995	2575				

Field changeable beam angles (25/40/55 degree) - reflectors provided
Lumens shown based on 40degree beam angle at 25 watts



CLICK TO VIEW PRODUCT

Notes: