

Clamps

Plenum-Rated Standard Clamp



- Ideal for copper, PEX and CPVC tubing
- Mounts directly on HoldRite™ Stout Bracket or other surfaces
- Meets ASTM E84 25/50 and UL 94 V-0 requirements (Plenum-rated)

Part number	Pipe size	Box qty
231-S	1/2 in. CTS	100
232-S	3/4 in. CTS	100

Variable Closure Isolation Clamp



- Lab-tested, sound-rated and isolation solution
- Compatible with copper, PEX, CPVC, iron pipe and other system materials
- Variable closure clamp mounts directly to HoldRite Stout Bracket™ SB1S/SB2S and EZ-STRUT™ Bracket
- Supports up to 2" pipe sizes, with load ratings up to 300 pounds
- Framework meets UL 94 V-2 flame rating
- Includes isolation pads to minimize noise and vibration
- Acoustic noise reduction data available

Part number	Pipe size	Box qty
250	Up to 1 in. CTS	50
280	1 in. - 2 in. CTS/IPS	50

- Lab-tested, sound-rated and isolation solution
- Compatible with copper, PEX, CPVC, iron pipe and other system materials
- Flat base, variable closure clamp mounts directly to HoldRite Stout Bracket™ #SB3 and #SB4 brackets, wood, metal or other flat surfaces
- Supports up to 2" pipe sizes, with load ratings up to 300 pounds
- Framework meets UL 94 V-2 flame rating
- Includes isolation pads to minimize noise and vibration
- Acoustic noise reduction data available

Part number	Pipe size	Box qty
255	Up to 1 in. CTS	50
285	1 in. - 2 in. CTS/IPS	50

Plenum-Rated Variable Closure Clamp



- Compatible with copper, PEX, CPVC, iron pipe and other system materials
- Load rating of up to 300 pounds
- Meets ASTM E84 25/50 rating and UL 94 V-0 requirements (Plenum-rated)

Part number	Pipe size	Box qty
250-S	Up to 1 in. CTS	50
255-S	Up to 1 in. CTS	50
280-S	1 in. - 2 in. CTS/IPS	50
285-S	1 in. - 2 in. CTS/IPS	50