



TECHNICAL INFORMATION



Stock



Recommend offset
pattern $\leq 33\%$



DCOF: ≥ 0.42



Frost Resistant



Made in USA



COLORS



Ash Concrete
CRV APAC



Ash Travertine
CRV APAT




Dove Concrete
CRV APDC



Dove Travertine
CRV APDT




Sand Concrete
CRV APSC



Sand Travertine
CRV APST



White Concrete
CRV APWC



White Travertine
CRV APWT



Statuario
CRV APSR

Tiles, Mosaic and Trim*

SIZE	ACTUAL	THICKNESS	FINISH
12" x 24"	11.81" x 23.81"	8.5mm	Matte/Natural
2" x 2" Mosaic	11.94" x 11.94"	8.5mm	Matte/Natural
4" x 24" Bullnose	3.75" x 23.81"	8.5mm	Matte/Natural

* Not all sizes are available in all colors and finishes.

Application**

		WALL	FLOOR
Interior	Residential	•	•
Interior	Commercial	•	•
Interior	Heavy Commercial	•	
Exterior	Residential/Commercial	•	

** These recommendations are not defined by ANSI Standards

Performance Characteristics

Breaking Strength	> 400lbf
Chemical Resistance	N/A
DCOF	≥ 0.42
Deep Scratch Resistance - Unglazed	N/A
Frost Resistance	Resistant
Mohs Hardness - EN101	N/A
Water Absorption	N/A
Certifications	Green Squared
Country of Origin	USA
Shade Variation Code	N/A



Please see virginiatile.com for details