

CyberPower

PDU13103 | BASIC PDU SERIES



Deliver reliable power to electronic equipment, servers, and network/telecom devices

Deliver reliable unfiltered power to connected equipment with the CyberPower PDU13103 basic 3-Phase PDU. Designed for data centers and other electrically demanding applications, this unit features rugged, industrial-grade metal housing, network-grade outlets and operates in high temperatures up to 140°F (60°C).

The PDU13103 supports a 200V-240V 20A input, includes 42 IEC outlets, and provides a maximum output load of 5.7kW. The CyberPower PDU13103 is protected by a three-year limited warranty.

TYPICAL APPLICATIONS

- Data Centers
- Corporate Servers
- Network Closets

FEATURES

- Phase: 3-Phase
- Amps: 20A (Derated to 16A)
- Volts: 200V-240V
- Max. Output Load: 5.7kW
- Frequency: 50/60Hz
- Input plug type: NEMA L21-20P
- Outlets: 36 x IEC-320 C13 + 6 x IEC-320 C19
- Size: 0U Rackmount
- Cord Length (ft): 10
- Dimensions (in): 2.2W x 70.5H x 2.2D
- Warranty: Three-Year

SPECIFICATIONS

INPUT	
Cord Length	10 ft (3.0 m)
Derated Input Current	16 A
Input Frequency Range	50 Hz - 60 Hz
Input Plug Type	NEMA L21-20P
Maximum Input Current	20 A
Nominal Input Voltage	200 - 240 VAC
Phase	3-Phase

OUTPUT	
Nominal Output Voltage	200 - 240 VAC
Outlet Type	36 x IEC-320 C13 6 x IEC-320 C19
Outlets - Total	42
Overload Protection	None

PDU13103

BASIC PDU SERIES

SPECIFICATIONS CONT.

PHYSICAL	
Adjustable Mounting Brackets	1 Set
Color	Black
Cord Retention Tray/ Cord Organizers	Yes
Form Factors Supported	OU Vertical Rackmount
Material of Construction	Metal
Rack Height	OU

PHYSICAL DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	5.59 x 179.07 x 5.59 cm
Physical Dimensions - Width/Height/Depth (mm)	56 x 1791 x 56 mm
Physical Dimensions - Width/Height/Depth (in.)	2.2 x 70.5 x 2.2 in.
Weight (kg)	5.72 kg
Weight (lbs.)	12.6 lbs.

SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	17.53 x 16.0 x 201.42 cm
Shipping Dimensions - Width/Height/Depth (mm)	175.26 x 160.02 x 2014.22 mm
Shipping Dimensions - Width/Height/Depth (in.)	6.9 x 6.3 x 79.3 in.
Shipping Weight (kg)	9.2 kg
Shipping Weight (lbs.)	20.1 lbs.

ENVIRONMENTAL	
Operating Elevation	0 - 11,480 ft (0 - 3,499 m)
Operating Relative Humidity	0 - 95 % (non-condensing)
Operating Temperature	23 - 140 °F (-5 - 60 °C)

CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL 60950-1 FCC Class A

WARRANTY	
Product Warranty	Three-Year Limited