## **Surface-mount Enclosures**

Model 238 Series and Model 236 Series



GAI-TRONICS offers a variety of enclosures designed to permit surface mounting of our \*\*\*flush-mount RED ALERT® and Industrial Telephones. These enclosures provide weather-proof protection for the telephone electronics and are aesthetically appealing.

Our **236 series** enclosure offers hooded protection from the elements and is available in three standard colors; black, red, and yellow (custom colors available). These enclosures are manufactured from non-corrosive aluminum and protected with a Polyurethane finish.

Our **Model 238** series enclosures combine aesthetics and durability in a brushed stainless steel design.

All of our surface-mount enclosures are suitable for indoor and outdoor use. The 236 series and Model 238-001 enclosures are designed to accommodate our full-size telephones and are compatible with our Model 231-002 Pole Mount Kit. The Model 238-001FS is designed to accommodate our compact (FS) series telephones and utilizes our Model 231-001FS Pole Mount Kit. Model 238-003 (not shown) accommodates our flush-panel behavioral-health telephones with model numbers containing BH that measure  $8.5 \, \text{H} \times 7.5 \, \text{W}$  inches; compatible with Model 231-001FS Pole Mount Kit.





**Model 238-001FS** (For Compact Series Telephones)



Model 238-001 (For Full-size Telephones)



Model 236-001YL (Yellow)\*







# **Surface-mount Enclosures**

**Model 238 Series and Model 236 Series** 

Model 236 Series (Full-size Telephones)



#### **SPECIFICATIONS**

model 250 belles (i dii size relepitor	nes)
Construction	
Finishing	Polyurethane paint
Mounting	Four 5/16-inch (0.312) diameter mounting holes in mounting bosses
Dimensions	$12.3 \text{ H} \times 10.31 \text{ W} \times 6.37 \text{ D}$ inches; $(312 \times 262 \times 162 \text{ mm})$ , maximum (top of shroud)

Cable Entrycustomer-providedShipping Weight3.5 lb. (1.6 kg) maximumInstallation Manual\*Pub. 42004-285

#### Model 238-001 (Full-size Telephones)

Construction	
Finishing	Brushed and passivated
Mounting	Four 5/16-inch (0.312) diameter mounting holes in mounting bosses
Dimensions	12.13 H $\times$ 10.18 W $\times$ 2.65 D inches (308 $\times$ 259 $\times$ 67 mm) maximum
Cable Entry	1-inch entry in rear of enclosure
Shipping Weight	
Installation Manual*	

### Model 238-001FS (Compact FS Series Telephones)

Construction	
Finishing	Brushed and passivated
Mounting	Four 5/16-inch (0.312) diameter mounting holes in mounting bosses
Dimensions	8.5 H $\times$ 6.5 W $\times$ 2.56 D inches (215 $\times$ 165.1 $\times$ 65.0 mm) maximum
Cable Entry	(2) 7/8-inch entries in rear or bottom of enclosure (seals provided)
Shipping Weight	
Installation Manual*	Pub. 42004-434

#### Model 238-003\*\*

Construction	
Finishing	Brushed and passivated
Mounting	Four 1/4-inch (6.4mm) diameter mounting holes in mounting bosses
Dimensions	8.5 H $\times$ 7.5 W $\times$ 2.56 D inches (215 $\times$ 190.5 $\times$ 65.0 mm) maximum
Cable Entry	(2) 0.86-inch entries in rear or bottom of enclosure (seals provided)
Shipping Weight	
Installation Manual*	Pub. 42004-539



Toll Free: 1 (800) 492-1212 Tel: (610) 777-1374 Fax: (610) 796-5954 www.gai-tronics.com
Tel: +44 (0)1283 500500 Fax: +44 (0)1283 500400 www.gai-tronics.co.uk
Tel: +39 02 48601460 Fax: +39 02 93663110 www.gai-tronics.com

Tel: +(65) 6282 2242 (Press 4 for GAI-TRONICS) www.gai-tronics.com a Tel: 011-61-28-851-5000 Fax: 011-61-29-899-2490 www.austdac.com.au













<sup>\*</sup> Manuals can be located on our website homepage at www.gai-tronics.com

<sup>\*\*</sup> Flush-panel behavioral-health telephones with model numbers containing BH that measure 8.5 H  $\times$  7.5 W inches