




# WINDOW AIR CONDITIONER

14,000 BTU | ELECTRONIC



## CHOOSING THE RIGHT AIR CONDITIONER

### 1 MEASURE AREA OF THE ROOM



CALCULATE ROOM SIZE  
room length x room width = sq. ft.

### 2 MATCH ROOM SIZE WITH CORRECT BTUs

SQ. FT.	ROOM SIZE	BTUs
150	10' x 15'	5,000
250	10' x 25'	6,000
350	17' x 20'	8,000
450	15' x 30'	10,000
550	20' x 27'	12,000
700	20' x 35'	14,000
1,000	25' x 40'	18,000
1,500	30' x 50'	25,000

### 3 MAKE ANY ADJUSTMENTS



INCREASE BTU 10%  
FOR SUNNY ROOMS. DECREASE  
BTU 10% FOR SHADED ROOMS.




ADD 600 BTUs  
FOR EACH ADDITIONAL  
PERSON OVER TWO.



ADD 4,000 BTUs  
IF UNIT IS USED IN  
A KITCHEN.

### 4 MEASURE WINDOW OPENING (HEIGHT & WIDTH)



2PNC14000	
UPC CODE	842149002466
COOLING CAPACITY (BTU)	14000
ENERGY STAR	No
COVERAGE AREA (sq. ft.)	700
CEER	11.8
VOLTAGE	115V
AMPS	11.8
WATTS	1280
WINDOW WIDTH (min/max) (in.)	23-36
WINDOW HEIGHT (min) (in.)	15.5
FAN SPEEDS (cool/fan)	3/3
UNIT DIMENSIONS (W×H×D) (in.)	21.5×14.75×19
PKG. DIMENSIONS (W×H×D) (in.)	23×17×22
WEIGHT (Net/Gross) (lbs.)	71/78.5
CONTAINER QTY. (40HQ)	498
REFRIGERANT	R32
OUTLET CONFIGURATION	
	15A - 115V

## FEATURES

- 3 cooling & 3 fan speeds
- 4-way adjustable air vents
- Cool, Fan, Eco, and Sleep modes
- Quick & easy installation
- Mounting kit included
- Electronic controls
- Follow-me remote control acts as portable thermostat
- 24-hour timer
- Auto-restart
- Adjustable thermostat (62-86°F)
- Easy clean tilt-out filter

