

James

BY SONANCE


QX SPL2 IN-WALL DATA SHEET

TECHNICAL SPECIFICATIONS

UOM	QX-SPL2 Each
Tweeter	1" (25mm) Soft Dome
Woofer	2" x 5" Carbon Fiber/Aluminum Honeycomb Racetrack
Frequency Response	120Hz-22kHz +/-3 dB
Impedance	4-8 ohms (woofer quantity dependent)
Power Handling (RMS)	5 watts minimum; 150 watts maximum
Sensitivity (2.83V/1m)	88dB SPL
Enclosure	Aircraft Grade Aluminum
Width (W)	Built to Order
Dims (Depth x H)	2.5" x 3" (63.5mm x 76.2mm)
Shipping Weight	Dependant on width


KEY FEATURES

- Built-to-order based on application and configuration to perfectly match TV size
- In-wall design with paintable grille
- 2" Low-profile height to fit limited wall space
- Available in stereo, left-right-center, or split into pairs with centergy technology
- 4 ohms for two/four woofer configurations, 8 ohms for one woofer configurations




3" (76.2mm)
Height

44.375" (1127.13mm) Min Cutout Width
QX-SPL2-LCR Front View



44.375" (1127.13mm) Min Cutout Width
QX-SPL2-LR Front View



44.375" (1127.13mm) Min Cutout Width
QX-SPL2-CS Front View

LIMITED FIVE (5) YEAR WARRANTY Sonance warrants to the first end-user purchaser that this Sonance-brand product ("Product"), when purchased from an authorized Sonance Dealer/Distributor, will be free from defective workmanship and materials for the period stated above. Sonance will at its option and expense during the warranty period, either repair the defect or replace the Product with a new or remanufactured Product or a reasonable equivalent. For more details please refer to the product manual.

©2025 Sonance. All rights reserved. Sonance is a registered trademarks of Dana Innovations. Due to continuous product improvement, all features and specifications are subject to change without notice. For the latest Sonance product specification information visit our website at www.sonance.com. JAMES by SONANCE • 2185 Park Place • Minden, NV 89423 • USA • PHONE: (775) 461-7500 • www.sonance.com 11.13.2025