



Realm II™ mirrors traditional honed marble with subtle veining and refined movement. Sophisticated colors with crackled and distressed details lend a natural aesthetic. A matte finish and various tile sizes make Realm II™ ideal for numerous interiors.

REALM II™

Glazed Porcelain



FLOOR / WALL  RESIDENTIAL  COMMERCIAL  INDOOR  OUTDOOR  POOL 



Assembly



District



Domain





Mosaics



Assembly


District

Domain

| | | | | | | | |
|----------------------------|---|---|---|---|--------------------|--------------------------|---------------------------|
| Sizes |  |  |  |  | | | |
| | 13"x13" 12.99"x12.99" | 12"x24" 11.81"x23.62" | 13"x13" Mesh | 3"x13" Floor SBN | | | |
| Thickness | 7.2mm | 9.8mm | 8mm | 8mm | | | |
| Faces | 11 | 10 | N/A | N/A | | | |
| Finish | Matte | Matte | Matte | Matte | | | |
| Edge | Pressed | Pressed | Cut | Cut/Rounded | | | |
| Grout Joint Recommendation | 3/16" | 3/16" | 3/16" | 3/16" | | | |
| Testing | Abrasion Resistance C1027 | Breaking Strength C648 | Chemical Resistance C650 | Water Absorption C373 | DCOF ANSI A1371 | Scratch Hardness MOHS | Shade Variation Rating |
| | III | >275 lbf | Resistant | ≤0.50% | >0.55 | 5 | V3 |

Product and Installation Details | ANSI A108.02
 Section 4.3.8.2 - For running bond/brick jointing patterns utilizing tiles (square or rectangular) where the side being offset is greater than 18" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the tile manufacturer. If an offset greater than 33% is specified, specifier and owner must approve mock-up and lippage.



 Sustainability Attributes

- Red List Free
- Health Product Declaration (HPD) provided upon request
- Product Packaging is 100% recyclable
- VOC Free
- Recycled Content 0% Pre- and Post-Consumer

*For more information visit www.emser.com. Always consult a professional for proper usage and installation.