

# FLUORESCENT FLUSH MOUNT FIXTURE ASSEMBLY & INSTALLATION INSTRUCTIONS

## MODEL#31014

*Please read carefully and save these instructions, as you may need them at a later date.*

### CAUTION

Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

### GENERAL

All electrical connections must be in accordance with local and national electrical code (N.E.C) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instruction.

### ASSEMBLY AND INSTALLATION

- Before installing, preset the nipple (16) length:
  - Thread the hex nut (14) onto the nipple (16), and screw the nipple (16) into the coupling (15) on the fixture pan (12) a minimum of four turns.
  - Place the center holes of the glass shade (17) and the cap (18) over the nipple (16) so that it protrudes out of the cap (18) 1/4 " . Remove the glass shade (17) and the cap (18) and secure the nipple (16) in place by tightening the hex nut (14).
- Pull the supply wires (5&6) and the house ground wire (7) out from the outlet box (1) and attach the mounting bracket (2) to the outlet box (1) using the slotted holes in the mounting bracket (2) and the mounting screws (3) provided.
- Thread the fixture screws (4) two full turns into the appropriate threaded holes in the mounting bracket (2). Check the mounting bracket (2) against the fixture keyhole slots (13) to ensure proper fit.
- Make the wiring connections: using the green screw (11), fasten the house ground wire (7) and the fixture ground wire (10) if provided, to the mounting bracket (2), as shown. Connect the white supply wire (5) to the white (or ribbed) fixture wire (8); connect the black supply wire (6) to the black (or smooth) fixture wire (9) using wire connectors (20).
- Carefully tuck all wires back into the outlet box (1). Locate the fixture pan (12) over the outlet box (1), positioning the fixture screw (4) heads through the large openings of the keyhole slots (13). Rotate the fixture pan (12) to seat the screws, and tighten securely. (See fig.2)

- Now you are ready to install the lamp. Install GU24 lamp (21) into the socket. Do not exceed recommended maximum wattage.
- Put the glass shade (17) through the threaded nipple. Then secure the cap (18) with the Finial knob (19).

### INSTALLATION IS NOW COMPLETED

