



ARCHITECTURAL & ENGINEERING SPECIFICATION

Polished chrome-plated cast brass faucet body with integral shanks, slow-closing metering cartridges, a 3-1/2" [89mm] centerline rigid or swing gooseneck spout, and vandalresistant ADA compliant color-coded metal handles. Easy adjustable cycle time, preset to 10 seconds at 60 PSI. Unit is furnished with a water-conserving aerator which reduces flow to .25 GPC [.95 L] (complying to ANSI A112.18.1 Standard for flow), mounting hardware, 1/2" NPSM coupling nuts for standard lavatory risers and integral shank filters.

\*Note: By nature, warm/hot water causes 1-2 seconds lower flow time than cold water.

Zurn Lead Free products (-XL) is the line of durable, high quality brass faucets and fixtures that are designed and manufactured to comply with Section 1417 of the Safe Drinking Water Act (SDWA) which mandates the weighted average lead content of no more than 0.25% of the wetted surface.

PRODUCT FEATURES

- Polymer Metering Cartridge Sleeve
- Chrome-plated cast brass widespread body
- Color Coded Brass Metering Handle
- Adjustable Cycle Timing

COMPLIANCE AND CERTIFICATION:

- Lead Free Compliant
- ADA Compliant



AERATOR OPTIONS

	FLOWRATE GPM [LPM]	VANDAL RESISTANT	PRESSURE COMPRESSION	OUTLET TYPE
<b>-3M</b>	0.5 [1.9]	☑	☑	Spray
<b>-7M</b>	1.0 [3.8]		☑	Spray
<b>-16M</b>	1.0 [3.8]	☑	☑	Spray
<b>-22M</b>	1.0 [3.8]	☑		Laminar
<b>-25M</b>	0.35 [1.3]	☑	☑	Spray
<b>-28M</b>	0.5 [1.9]	☑		Laminar

\*Note: 0.35 GPM aerator typically maxes out around 10 second run time

SUFFIX OPTIONS

- 140 140° Restricted Swing Gooseneck Spout
- G 1-1/4" [32mm] Grid Strainer Drain
- ICT Inter-connecting Copper Supply Tubes for 8" In-line Centers
- IN Institutional Handle - Tamper-Proof and Vandal-Resistant
- P 1-1/4" [32mm] Pop-up Drain
- RKR ADA Compliant Rocker Handle

ARCHITECTURAL & ENGINEERING APPROVAL

The information contained in this document is subject to change without notice. Please contact Zurn for most up to date information.

Rough-in/Overview dimensions

