

DIAMONDS



FIELD TILES		
SIZE	SIZE SPECIFICATIONS	THICKNESS*
FLAT TILE		
8"x4"	7.834"x3.937" (199mm x 100mm)	0.354" (9mm)
PILLOW TILE		
8"x4" Pillow	7.834"x3.937" (199mm x 100mm)	0.567" (14.4mm)
FLAT DOT		
3/4"x3/4"	0.827"x0.827" (21mm x 21mm)	0.354" (9mm)
SPHERE DOT		
3/4"x3/4"	0.787"x0.787" (20mm x 20mm)	0.622" (15.8mm)
APPLICATIONS		
	SUITABLE RESIDENTIAL	SUITABLE COMMERCIAL
Bathroom Walls	YES	YES
Shower Walls	YES	YES
Kitchen Walls	YES	YES
Countertops	NO	NO
Fireplace Surrounds**	YES	YES
Outdoor Cooking / Bar Spaces	YES	YES
Pool Waterlines / Water Fountains	NO	NO
Floors	NO	NO
PERFORMANCE CHARACTERISTICS		
	TEST METHOD ATSM / ISO	RESULT
Water Absorption	C-373 / 10545-3	Pass
Breaking Strength	C-648 / 10545-4	Pass
Chemical Resistance	C-651 / 10545-14	Resistant
Facial Dimensions	C-499 / 10545-2	Pass
Range of Thickness	C-499 / 10545-2	Pass
Warpage	C-485 / 10545-2	Pass

DIAMONDS

INSTALLATION	
GROUT JOINT RECOMMENDATION	SHADE VARIATION
1/8"	V1 - Uniform Appearance

CLEANING RECOMMENDATIONS
Routine with a non-abrasive/non-acidic, mild and PH neutral cleaner

CHARACTERISTICS	
Glaze	Solid
Surface Sheen	Glossy
Texture	Smooth

*Thickness is understood as the highest point of the tile.

**This usage excludes the Silver Diamonds.

Due to the nature of our tile, a certain amount of variation in color, shading, surface and texture are to be expected.