ALLIED MOULDED PRODUCTS, Inc.
222 N Union Street • Bryan, OH 43506
Ph: (800) 722-2679 • Fx: (800) 237-7269
Email: sales@alliedmoulded.com
www.alliedmoulded.com

3303-NKV



VIDEO

Product Description

Three gang electrical box for use with nonmetallic sheathed cable

Brand: fiberglassBOX™ - Vapor Seal
Catalog #: 3303-NKV

Height: 3-3/4 in.
Width: 5-11/16 in.
Depth: 3-9/16 in.
Volume: 56.5 cu. in.
Type of Installation: New Work
Wall Box
Number of Gangs: 3

Carton Quantity: 18
Carton Weight: 17 lb.

UPC: 085339152095
UNSPSC: 39121308
Patents:
U.S. Patent No. 6,908,003 B2
Country of Origin: United States of America

FEATURES

Polyurethane flange for single drywall offset, machine tapped device holes, slot provision for low voltage divider, leveling ribs, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps factory installed

APPLICATION

New work residential construction 2 HR fire resistive walls - air-sealed electrical boxes for envelope walls in Energy Star homes

STANDARDS

ANSI / UL 514C: File No. E30594

FIRE CLASSIFICATION

Fire Test of Building Construction Materials
ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)
Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less
Shall be separated by a horizontal distance of not less than 3 inches
Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)

COLOR

Beige/tan

MATERIAL

Fiberglass reinforced polyester BMC

MOUNTING

Angled mid nails

ADDITIONAL MATERIALS

Carbon steel fasteners

Polyvinyl chloride clamps

Polyurethane flange

© 2015 Allied Moulded Products, Inc.