

LOC RIM DRUM SPECIFICATION SHEET

GALLON CAPACITY	17	
INSIDE DIMENSIONS (DIAMETER X HEIGHT) ...	15 ½" x 21"	
OUTSIDE DIMENSIONS (DIAMETER X HEIGHT) ...	16 ¾" x 22"	
TARE WEIGHT	10 lbs. (Approx.)	
SIDEWALL	GRADE	56# Linerboard
	ADHESIVE	Sodium Silicate
	LINING/BARRIER	N/A
	PLYS	8 Plys Total
	TEST	1,200 psi
PACKAGING WEIGHT LIMIT	600 lbs.	
BOTTOM HEAD ELEMENT	TYPE	Laminated Fiber
	CALIPER	0.220"
	MULLEN	1,300 psi
	LINING/BARRIER	N/A
BOTTOM CHIME	TYPE	Steel
	GAUGE	24 Ga.
	FINISH	Electro Galvanized
COVER OR TOP HEAD	TYPE	Steel with Gasket
	CALIPER/GAUGE	24 Ga.
	MULLEN/FINISH	Gold Lacquer
TOP CHIME	TYPE	Steel
	GAUGE	24 Ga.
	FINISH	Electro Galvanized
CLOSURE	TYPE	Loc Ring (Steel)
	GAUGE	24 Ga.
	FINISH	Electro Galvanized
	LOCK	Top Latch
CAPACITY IN CUBIC INCHES	3,927	
CAPACITY IN CUBIC FEET	2.27	
ADDITIONAL FEATURES	Heat seal tape over inside seam.	

NOTE: All dimensions listed on the above drum are nominal. Kraft paper is subject to change with variances in relative humidity. Diameters can vary +/- 1/16". Height tolerances can vary +/- ¼" per ft. of drum sidewall. Weight variances can vary +/-5%. All thicknesses and other dimensions are nominal unless otherwise stated.

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



REF NO.:

DWG31139

DESCRIPTION:

17 Gallon Kraft Fiber Aluminum Lined OH Drum,
with Steel Cover