

T-REX® DOUBLE SIDED SUPER GLUE TAPE WITH HIGH-TACK ACRYLIC ADHESIVE

TYPICAL APPLICATIONS

- For fast fixes
- A great alternative to glue for mounting and automotive solutions and for repairs requiring two surfaces to be adhered to each other;
- Use on a variety of surfaces, including ceramic, concrete, glass, fabric, metal, plastic, tile, wood and more

PRODUCT FEATURES

- Heavy-duty acrylic adhesive permanently bonds on contact to a variety of surfaces including ceramic, concrete, glass, fabric, metal, plastic, tile, wood and more for quick, lasting repairs
- Unlike traditional super glue, double-sided adhesive tape will not stain surfaces
- Tape can be torn by hand for easy, hassle-free application
- High-tack tape does not bond to skin and is safer to use than traditional super glue
- Withstands extreme weather and temperatures ranging from 0 F to 175 F for indoor and outdoor use

CONSTRUCTION

Backing: Polyester film

Adhesive: Acrylic-based

Liner: Coated paper

STANDARD WIDTH

0.75 in

19 mm

STANDARD LENGTH

5 yd

4.57 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

APPLICABLE STANDARDS

NA

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR



PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Stainless Steel - Exposed Side	180 oz/in width	19.7 N/10mm
Adhesion to Stainless Steel - Liner Side	180 oz/in width	19.7 N/10mm
Application Temperature Range	50 F to 100 F	10 C to 38 C
Service Temperature Range	0 F to 175 F	-18 C to 80 C
Thickness	7.5 mil	0.19 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

