

Bluestone

Porcelain Stone®

Color Palette



AV201 ▶ Colorado Buff UPS




AV201 ▶ Colorado Buff HON




AV202 ▶ Arizona Brown UPS



AV202 ▶ Arizona Brown HON



AV203 ▶ Pennsylvania Blue UPS



AV203 ▶ Pennsylvania Blue HON



AV204 ▶ Vermont Black UPS



AV204 ▶ Vermont Black HON

Features and Benefits

- UPS and honed finishes add to design versatility
- All sizes are rectified and modular with a minimum of 3mm grout joint
- Cross-Sheen® finish for easy cleaning (available on UPS only)

Get Planked!

Our Porcelain Stone® products are available in popular plank shapes with no minimum order and quick fulfillment. Depending on the product, there are up to 4 widths and 7 lengths, creating more than 2,796 combinations.



AV204 ▶ Vermont Black UPS 24 x 24



Bluestone

Porcelain Stone®

Sizes & Finishes

Field Tile

Nominal (in)	Actual (mm)	Thickness (mm)	Grout Joint (mm)	Finish
6 x 6	147 x 147	10.5	3	UPS/HON
6 x 24	147 x 597	10.5	3	UPS/HON
12 x 12	297 x 297	10.5	3	UPS/HON
12 x 24	297 x 597	10.5	3	UPS/HON
24 x 24	597 x 597	10.5	3	UPS/HON

Note: All field tile is rectified and modular with a minimum of 3mm grout joint. Actual measurements stated in inches indicate tile is calibrated (non-rectified). Actual measurements stated in mm indicate tile is rectified. HON (Honed finish) is semi-polished.

Coordinating Trim


Nominal (in)	Actual (mm)	Thickness (mm)	Grout Joint (mm)	Finish
4 x 12 Single Bullnose	97 x 297	10.5	3	UPS/HON
6 x 12 Cove Base	150 x 372	10	3	UPS
6 x 8 Cove Base Corner	150 x 200	10	3	UPS



4 x 12 Bullnose



6 x 12 Cove Base
(Universal, flat top)



6 x 8 Cove Base Corners

Mosaics

Nominal (in)	Actual (mm)	Sheet (mm)	Thickness (mm)	Finish
2 x 2*	47 x 47	297 x 297	10.5	UPS
3 x 6**	72 x 147	297 x 272	10.5	HON
Random***		297 x 322	10.5	
2 x 2	47 x 47		10.5	UPS/HON
2 x 4	47 x 97		10.5	Mixed
2 x 6	47 x 147		10.5	

* 2 x 2 mosaic tile in 297mm x 297mm mounted sheets

** 3 x 6 mosaic tile in 297mm x 372mm mounted sheets (staggered joints)

*** 2 x 2, 2 x 4 and 2 x 6 mosaic tile in 297mm x 322mm mounted sheets

Product Performance


Breaking Strength	>450 lbf	ASTM C648
Bond Strength	>200 psi	ASTM C482
Chemical Resistance	Unaffected	ASTM C650
Frost Resistance	Resistant	ASTM C1026
Water Absorption	<0.20%	ASTM C373
Scratch Hardness	7	Mohs Scale

Wet Dynamic COF

HON	.42 – .52	DCOF AcuTest™
UPS	.50 – .60	DCOF AcuTest™

Shade & Texture Index

Bluestone has a shade variation of V2.



V1 Uniform appearance

V2 Slight Variation

V3 Moderate Variation

V4 Substantial Variation

Sizes (Shown in AV201 Colorado Bluff)

24 x 24




12 x 24



6 x 24



12 x 12



6 x 6



2" x 2" Mosaics.
Available in UPS Finish
Only. Mounted on an
297mm x 297mm
sheet.)



Random Mosaics*
Available in UPS &
HON Mix. Mounted on
an 297mm x 322mm
sheet.)



3" x 6" Mosaics *
Available in HON Finish
Only. Mounted on an
297mm x 372mm sheet.)



Bluestone

Crossville, Inc.

PO Box 1168
Crossville, TN
38557

Phone 931.484.2110
Fax 931.456.2956
E-Mail Crosscc@CrossvilleInc.com
Web CrossvilleInc.com

Recommended Use

Bluestone is recommended for interior floors, walls, countertops, and exterior walls in both residential and commercial applications. Bluestone is not recommended for exterior horizontal surfaces or exterior paving. If offset pattern is required for tiles 18 inches or longer, Crossville® recommends an offset of not greater than 33%. If an offset greater than 33% is specified, specifier and owner must approve mock-up and lippage. See CrossvilleInc.com for detailed installation instructions.

Wet Area Use For Mosaic Tiles

Crossville® produces Bluestone mosaic tiles with the Cross-Sheen® finish. The AcuTest™ Wet Dynamic COF is ≥ 0.42 . Their small sizes ensure frequent grout joints which provides traction and drainage. Crossville cannot control situations involving incorrect installation, improper slope to the drain for elimination of standing water, and poor surface cleaning.

This information is provided so that customers may make a realistic and informed decision when comparing Crossville's mosaics to other tile products in wet area environments, such as residential/commercial bathrooms, showers, and interior pool decks.

Care and Maintenance

Regular cleaning is the best way to keep Bluestone tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth. No waxes are needed. More information regarding the care and maintenance of Crossville® products is available at CrossvilleInc.com.

Green Squared™ Certified

com. Crossville® has earned Green Squared™ certification from the Tile Council of North America (TCNA) for its entire U.S.-manufactured porcelain product line-up, as well as its manufacturing processes. The company is among the first ever recipients of this certification standard for the tile industry. TCNA developed the Green Squared certification under American National Standards Institute (ANSI) process. The multi-attribute program (ANSI A138.1) scores products in five categories of performance: product characteristics, manufacturing, corporate governance, innovation and end-of-life. Crossville's certified products and processes received stringent evaluation from Scientific Certification Systems (SCS), the green building industry's longest standing third-party certifier.

Hydrotec™

Our porcelain tiles are available with Hydrotec™. Crossville's revolutionary invisible coating harnesses the power of light, water, and oxygen to create the best defense against dirt and pollution. Whether indoors or out, floors and walls stay cleaner, providing a superior experience in any space. For complete details check our website at CrossvilleInc.com.



Our Warranty

Crossville Inc guarantees that its products will meet or exceed the performance specifications outlined in ANSI A137.1-2012 and in the performance data section of the Crossville, Inc. general product catalog. For complete details check our website at CrossvilleInc.com.

National Accounts

For over 20 years we have been offering Porcelain tile to commercial customers at National Accounts pricing programs with special discounts. The National Accounts department provides materials forecasting, sales support and samples.

Exterior Cladding

Crossville's Porcelain Stone® Exterior Cladding Systems are suitable for virtually any conventional masonry application. When used in conjunction with our exterior cladding systems, Crossville's Porcelain Stone offers clear advantages: decreased construction costs, less site disturbance, low-to-zero maintenance after installation, accelerated construction schedules and greater strength than traditional masonry.

▶▶ Crossville® Sample Express

Sample fulfillment & Help Line
Samples@CrossvilleInc.com
1 800 221.9093

Loose Samples for
Architects & Designers

Loose Tile Samples
Sizes may vary depending on product series
Max. of 4 large field tile per order

Replacement Chips for PSS Rack
Max. of 5, 2 x 2 chips per color

Standard Shipping
UPS Ground

Information listed here is subject to change. Please refer to CrossvilleInc.com for the latest, most accurate information.

Trade Organizations



Environmentally Aware

