



1. MAXIMUM MOUNTING PATTERN IS 36.7" (932 mm) WITHOUT REVERSING UPRIGHTS
2. MAXIMUM MOUNTING PATTERN IS 42.1" (1070 mm) WITH REVERSING UPRIGHTS
3. FOR RECESSED APPLICATIONS, MINIMUM VERTICAL LIFT FOR HOOK ENGAGEMENT IS .75" (19 mm)

THE INFORMATION AND DESIGNS CONTAINED IN THIS DRAWING ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF MILESTONE AV TECHNOLOGIES NEITHER THIS DESIGN NOR ANY INFORMATION CONTAINED IN THIS DRAWING MAY BE REPRODUCED OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF MILESTONE AV TECHNOLOGIES.

| | | | | | | | |
|--|-----|------------|--|--------------|--------------------------------|---|-------------------|
| CAD GENERATED DRAWING, DO NOT MANUALLY UPDATE. | | | | CHIEF | | 6436 CITY WEST PKWY EDEN PRAIRIE MN, 55344 PHONE: 866-977-3901 FAX: 877-894-6918 | |
| DRAWN BY | JAB | 06/06/2014 | DESCRIPTION XTM1U CUSTOMER DRAWING | | | | |
| ENG APPROVAL | | | MODEL NO. XTM1U | | | | |
| MFG APPROVAL | | | SCALE 1:8 | | | | |
| QA APPROVAL | | | SIZE B | | DWG. NO. TECH-000619 | | REV. 01 |
| SHEET 1 OF 1 | | | | | | | |