

MTG 200C



T-REX® STRONG AND CLEAR MOUNTING TAPE

TYPICAL APPLICATIONS

- Indoor/Outdoor mounting tape works on a variety of surfaces including metal, glass, wood, concrete, brick, tile, and ceramic
- Offers an easy alternative to nails, screws, staples or glue
- Designed specifically to hold longer and stronger for projects both big and small

PRODUCT FEATURES

- Thick, aggressive adhesive is designed to hold up to 2 lbs per 4 in of tape
- Clear, double-sided mounting tape holds longer and stronger for discreet, heavy-duty mounting applications
- Permanent application to a variety of indoor and outdoor smooth and rough surfaces including metal, glass, wood, concrete, brick, tile, ceramic and plastic*
- Weather-resistant tape withstands extreme temperatures ranging from -40 F to 200 F for year-long durability
- *Will not stick to all grades of plastic, including polyethylene and polypropylene plastics

CONSTRUCTION

Backing: Foam with Polyethylene Release Liner
Adhesive: Double Sided Acrylic Based

STANDARD WIDTH

1 in
25.4 mm

STANDARD LENGTH

60 in
1524 mm

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

APPLICABLE STANDARDS

NA

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR



PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Stainless Steel	18 lb/in width	1.97 N/10 mm
Application Temperature Range	50 F to 100 F	10 C to 38 C
Service Temperature Range	-40 F to 200 F	-40 C to 93 C
Tensile	85 lbs/in width	148.9 N/10 mm
Thickness	39 mils	0.99 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

