




SCP PART#: 16/4SP-26-BL UPC: 810070010560

DESCRIPTION:

4C/16 AWG 26 STRAND BC STANDARD SPEAKER CABLE, EN50575 Eca, PVC JKT- BLUE - 500FT/152M BOX



Regulatory

UL : UL 444 & UL 13, Type (UL) CMR/CL3 c(UL)
EU RoHS 2011/65/EU Compliant
EN50575: 2014 REACTION TO FIRE CLASS Dca

Construction Characteristics:

Conductor	Material	Stranded Bare Copper
	Size	16AWG X 4C(1.31mm ²)
	Construction	26/0.254mm +/-0.004mm
Insulation	Material	PVC
	Min.Thickness	0.30mm
	AVG.Thickness	0.33mm
	Diameter	2.0mm +/-0.10mm
	Colors	Black & Red & Green & White
Jacket	Material	PVC
	Min.Thickness	0.54mm
	AVG.Thickness	0.60mm
	Diameter	6.1mm +/-0.20mm
	Rip Cord	Nylon
	Color	Per request
Bend radius	Min 15D/96mm	

Electrical & Physical Characteristics:

Operating Temperature Range	- 20°C + 75°C
Minimum installation temperature	0°C + 40°C
Conductor Resistance	Max 15.5 ohm/km at 20°C
Insulation Resistance	Min 50MΩ*km at 20°C
Dielectric Strength	Min AC1.5KV
Rated Voltage	300V
Test Voltage	800V/min



Structured Cable Products®

Quality Installations Deserve Quality Products

www.spcat5e.com
sales@scpat5e.com
Direct: 954-327-5770
Toll Free: 866-470-5742

SCP PART#: 16/4SP-26-BL	UPC: 810070010560
--------------------------------	-------------------

DESCRIPTION:

4C/16 AWG 26 STRAND BC STANDARD SPEAKER CABLE, EN50575 Eca, PVC JKT- BLUE - 500FT/152M BOX

Marking:			
STRUCTURED CABLE PRODUCTS --- 16/4SP-26 --- E198137 SCP3 (UL) CL3 C(UL) CMR 4C 16AWG 26 STRAND OXYGEN FREE COPPER - EN50575:2014 CE Dca PVC JKT FT4 75C RoHS ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 ***FEET			
Packaging:			
Approx.Weight	Approx.Dimension(mm)	Package	Packages per pallet
11.6kgs/25.573lbs	320X260X320	500ft/ Box	36