

# 1080P Indoor/ **Outdoor Varifocal Dome Camera**

Data Sheet

ADC-VC847PF www.alarm.com

© 2021 Alarm.com. All rights reserved. 210527

# **Specifications**

Supported resolutions: 1920x1080, 1280x720, 640x360

Local recording: SVR and Onboard Recordina\*

Image sensor: 1/2.7" progressive scan CMOS

Lens: 3.2 mm(W) - 9.8 mm(T), F1.8 - F3.3

Field of view: 116° to 34°

Iris: P-iris

Remote varifocal control: Focal length, Manual focus adjustment, Autofocus

**Angle adjustment:** Pan: 0° to 350°; Tilt: 0° to 55°; Rotation: 0° to 180°

Low-light sensitivity: O lux with IR

**IR range:** Up to ~95 feet (30 meters)

Image adjustments: Flip, brightness, contrast, saturation, sharpness, exposure

Ethernet connection: 10/100 Mbps RJ-45

Operating temperature: -22°F to 122°F (-30°C to 50°C)

Operating humidity: 20% - 100% non-condensina RH

Power: 12 VDC ± 10% or PoE (802.3af), 10 W

Dimensions (WxH): 4.7 × 3.9" (11.9 x 10.0 cm)

Weight: 21.0 oz (594.5 g)

Ingress protection: IP66

Impact protection: IK10

Compliance: FCC, IC, C-Tick, CE Class B, UL



#### PRO SERIES

# Overview

The VC847PF is a PoE dome camera with a motorized varifocal lens, offering greater installation flexibility in indoor and outdoor environments and allowing user to remotely adjust how wide or narrow they want the camera's field of view without any loss of quality. The camera comes with a dark gray cover that can be optionally attached to change the appearance of the camera for aesthetic purposes. As part of the commercial Pro Series line, the camera enables intelligent analytics for object detection and business activity tracking. In addition to cloud clip storage, the VC847PF supports 24/7 recording to an optional onboard microSD card and/or the Commercial-Grade Stream Video Recorder (CSVR126).

#### Features

- Power over Ethernet
- IR night vision
- Business Activity Analytics
- Onboard Recording with Smart View
- Video Analytics with Object Detection
- 1080p HDR video
- IP66-rated waterproof & dust-tight

## **Business Activity Analytics**

**Occupancy + People Counting -** Measure occupancy and foot traffic. Receive a notification when real-time occupancy reaches a specified threshold.

People Counting - Measure foot traffic through a certain area. Count how many people cross a virtual line in one direction.

Queue Monitoring - Monitor people waiting in line. Receive a notification when the number of people in line or average wait time reaches a specified threshold.

Crowd Gathering - Monitor large groups. Receive a notification when the crowd size reaches a specified threshold

Heat Mapping - Visualize where people spend the most time within an area during a specified date and time range using a heat map.

# **Onboard Recording with Smart View**

Record encrypted, 24/7 HD footage locally on the camera with a microSD card. View live and recorded video on the Alarm.com website and mobile app from anywhere, using the SmartView video timeline to search for important events such as person detected or door accessed, and jump straight to the corresponding footage.

Approximate days of recordina

, ipproximate adjo or recording					
Recording Quality	32GB	64GB	128GB	256GB	
1920x1080 30FPS	1 Day	2 Days	5 Days	10 Days	
1920x1080 15FPS	2 Days	4 Days	7 Days	15 Days	
1280x720 10FPS	4 Days	7 Days	15 Days	29 Days	
640x480 10FPS	7 Days	15 Days	29 Days	59 Days	

### Included accessories

- Camera
- Dark Gray Cover
- Mounting hardware
- Torx wrench
- Water-resistant cap
- Cloth

\*Visit answers.alarm.com for the most up-to-date list of supported microSD cards.

Recording days cannot be guaranteed and will vary depending on the amount of motion in the scene.