



GE
Lighting

SAFETY & PERFORMANCE

- ☞ cUL_Listed
- ☞ NR_Can
- ☞ UL_Cls_P
- ☞ UL_Listed
- ☞ UL_Type1_Out
- ☞ UL_Type_HL
- ☞ FCC_Part_18
- ☞ Pro_comp_res_req

74472 - GE LFL Multi-Volt ProLine™ Electronic Program / Rapid

Start Ballast

GE240PS-MV-N

- ☞ High performance electronic ballast for all general fluorescent applications
- ☞ Multi-Voltage Technology handles voltage from 120 to 277V
- ☞ Light-weight, Low Profile Housing
- ☞ Parallel lamp operation means system maintenance is easier to manage

Product Photo



SPECIFICATIONS BY LAMP & WATTAGE

Lamp	# of Lamps	Line Volts	System Watts	Nom. Line Current	System Ballast Factor	Ballast Efficacy Factor	Power Factor% ($\geq$)	Crest Factor ($\leq$)	THD% ($\leq$)	Min. Starting Temp (F/ C)
F20T12	1	120	28	0.24			0.99	1.7	9	50
F20T12	1	277	29	0.13			0.92	1.7	17	50
F20T12	2	120	46	0.39	1.0	2	0.99	1.7	8	50
F20T12	2	277	45	0.18	1.0	2	0.94	1.7	11	50
F30T12	1	277	37	0.16			0.94	1.7	11	50
F30T12	1	120	37	0.31			99.0	1.7	8	50
F30T12	2	277	58	0.22	0.95	2	0.96	1.7	10	50
F30T12	2	120	60	0.31	0.95	2	99.0	1.7	7	50
F30T12/WM	1	120	30	0.26			0.99	1.7	12	50
F30T12/WM	1	277	30	0.13			0.82	1.7	27	50
F30T12/WM	2	120	50	0.42	0.95	2	0.99	1.7	9	50
F30T12/WM	2	277	50	0.2	0.95	2	0.91	1.7	18	50
F34T12	1	120	41	0.35			0.99	1.7	8	50
F34T12	1	277	41	0.17			0.94	1.7	11	50
F34T12	2	120	63	0.56	0.87	1	0.99	1.7	7	50
F34T12	2	277	62	0.26	0.87	1	0.96	1.7	10	50
F40T10	1	277	42	0.17			0.88	1.7	16	50
F40T10	1	120	42	0.35			0.99	1.7	10	50
F40T10	2	120	75	0.63	0.88	1	0.99	1.7	7	50
F40T10	2	277	72	0.27	0.88	1	0.94	1.7	16	50
F40T12	1	120	48	0.41			0.99	1.7	7	50
F40T12	1	277	48	0.19			0.95	1.7	10	50
F40T12	2	277	73	0.3	0.89	1	0.97	1.7	10	50
F40T12	2	120	74	0.67	0.89	1	0.99	1.7	6	50