

RSW 800



T-REX® HEAVY-DUTY, EXTRA-WIDE WATERPROOF AND REPAIR TAPE

TYPICAL APPLICATIONS

- Drain pan repair
- Large receptacle repair
- Drain pipe repair
- Equipment repair
- Water protection
- Containment sheeting patch
- Plumbing system leak
- Upholstery repair

PRODUCT FEATURES

- Heavy-duty repair tape is thinner than most waterproofing tapes without compromising on quality; extra width discreetly conforms to a variety of large and small objects
- The only waterproof tape that can be torn by hand with a liner-free backing for hassle-free application
- Shockingly strong, high-performance acrylic adhesive adheres to smooth and rough or difficult surfaces such as plastics, metals and more; initially repositionable for additional ease of use
- Instantly seals out water, air and moisture; performs when wet and in underwater applications
- Extreme weather performance and UV-resistance in heat, cold, rain and snow and wide application temperature range from 20 F to 120 F with long-term performance after install in high or freezing temperatures

CONSTRUCTION

Backing: Polyolefin Film

Adhesive: Solventless UV Acrylic Adhesive

STANDARD WIDTH

4 in

101.6 mm

STANDARD LENGTH

10 ft

3.05 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

NA

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLORS



Black
(BLK)



White
(WHI)



Clear
(CLR)

PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Stainless Steel	150 oz/in width	16.42 N/10 mm
Application Temperature Range	20 F to 120 F	-7 C to 49 C
Elongation	900%	900%
Service Temperature Range	-20 F to 190 F	-29 C to 88 C
Tensile	15 lbs/in width	26.3 N/10 mm
Thickness	13 mil	0.33 mm

Physical and performance characteristics shown above are obtained from tests recommended by PTSC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent product specifications or a guarantee of product performance. Individual rolls may vary from these standards (or physical properties). The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.



This tape is not designed to withstand water pressure.