HUBBELL
Power Systems

Deadend, Straight line, Spring Loaded, Side opening, #4 (7 STR) - 4/0 (19 STR) AL, #6 (6/1) - 4/0 (6/1) ACSR



By ANDERSON
Catalog # ASOD5701N

Deadend, Straight line, Spring Loaded, Side opening, #4 (7 STR) - 4/0 (19 STR) AL, #6 (6/1) - 4/0 (6/1) ACSR, Conductor Range 0.19 - 0.57 in, Fitting: None.

Features

Spring Loaded Vertical Keeper for Easy Installation, Add "S" for socket or "C" for clevis fitting options

General

Catalog Number	ASOD5701N
Fitting Type	None
Material	Aluminum Alloy; Steel
Material - Body	356 T6 Aluminum Alloy
Material - Bolt	Galvanized Steel
Material - Hardware	Galvanized Steel
Material - Keeper	356 T6 Aluminum Alloy
Product Category	Straight Line
Strength Rating - Ultimate	8000 lb
Body	
Style	ASOD
Type	Bolted
U-Bolts	1
UPC	096359363347

Dimensions

Diameter - Bolt	0.5 in
Diameter - Pin	0.625 in
Length	8.62 in
Weight	1.95 lb
Width	0.7 in

Conductor Related

Conductor Diameter - Maximum	0.57
Conductor Diameter - Minimum	0.19
Conductor Diameter Range	0.19 - 0.57

Certifications And Compliance

Buy America(n) Qualified	TAA Compliant (All status valid till December 2024)

Logistics

Pallet Quantity	600

Product Assets

Catalog Page - ASOD Catalog Page
Catalogs - Distribution Connectors
Installation Manuals - ASOD_install instructions
Literature - Deadends For Overhead Connections
Literature - Ropes Course Industry Letter (April 2021)
Sales Drawings - AL, Side Opening Deadend Clamp (CC-17236)
Specifications - ASOD5701N

©2025 Hubbell Incorporated. All rights reserved