Product data sheet
Characteristics

M9F11310
Miniature circuit breaker (MCB), Multi9 C60N, 3P, 10A, C curve, 10kA (IEC/EN 60947-2)

Main

Range	Multi9
Product name	Multi9 C60
Product or Component Type	Miniature circuit-breaker
Device short name	C60N
Device Application	Distribution
Poles description	3P
Number of protected poles	3
Line Rated Current	10 A 122 °F (50 °C) EN/IEC 60947-2
Network type	AC DC
Network Frequency	50/60 Hz
Trip unit technology	Thermal-magnetic
Curve code	C
Breaking capacity	30 KA Icu <= 125 V DC EN/IEC 60947-2 10 KA Icu 415 V AC 50/60 Hz between phases EN/IEC 60947-2 20 KA Icu 240 V AC 50/60 Hz between phases EN/IEC 60947-2 6 kA Icu 440 V AC 50/60 Hz between phases EN/IEC 60947-2
Utilisation category	Category A EN/IEC 60947-2
Standards	EN/IEC 60947-2
Product certifications	EAC[RETURN]KC[RETURN]CCC

Complementary

[Ue] rated operational voltage	240 V AC 50/60 Hz between phases 415 V AC 50/60 Hz between phases 440 V AC 50/60 Hz between phases <= 125 V DC
Magnetic tripping limit	8.5 x In +/- 20 % AC 12 x In +/- 20 % DC
[Ics] rated service breaking capacity	7.5 KA 75 % EN/IEC 60947-2 - 415 V AC 50/60 Hz 16 KA 75 % EN/IEC 60947-2 - 240 V AC 50/60 Hz 4.5 KA 75 % EN/IEC 60947-2 - 440 V AC 50/60 Hz 30 kA 100 % EN/IEC 60947-2 - <= 125 V DC
Limitation class	3
[Ui] rated insulation voltage	500 V AC 50/60 Hz EN/IEC 60947-2
[Uimp] rated impulse withstand voltage	6 kVEN/IEC 60947-2
Suitability for isolation	Yes EN/IEC 60947-2
Contact position indicator	Yes
Control Type	Toggle
Local signalling	ON/OFF indication
Mounting Mode	Clip-on
Mounting Support	DIN rail
9 mm pitches	6
Height	3.2 in (81 mm)
Width	2.1 in (54 mm)
Depth	2.8 in (72 mm)
Net Weight	0.79 lb(US) (0.36 kg)
Color	Gray

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Mechanical durability	20000 cycles
Electrical durability	10000 cycles
Provision for padlocking	Padlockable
Connections - terminals	Tunnel type terminal top or bottom) 0.002…0.04 in² (1…25 mm²) - rigid Tunnel type terminal top or bottom) 0.002…0.04 in² (1…25 mm²) - flexible Tunnel type terminal top or bottom) 0.002…0.04 in² (1…25 mm²) - flexible with ferrule
Wire stripping length	0.6 in (14 mm) for top or bottom connection
Tightening torque	17.7 lbf.in (2 N.m) top or bottom
Earth-leakage protection	Separate block

Environment

Heat dissipation	5.4 W 415 V - 10 A
IP degree of protection	IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529
Pollution degree	3 EN/IEC 60947-2
Overvoltage category	IV
Tropicalisation	2 IEC 60068-1
Relative humidity	95 % 131 °F (55 °C)
Ambient air temperature for operation	-22…158 °F (-30…70 °C)
Ambient Air Temperature for Storage	-40…176 °F (-40…80 °C)

Ordering and shipping details

Category	US10DE200908
Discount Schedule	0DE2
GTIN	3606480576379
Returnability	No
Country of origin	BG

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.13 in (5.400 cm)
Package 1 Width	2.95 in (7.500 cm)
Package 1 Length	3.35 in (8.500 cm)
Package 1 Weight	10.899 oz (309.000 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	4
Package 2 Height	3.15 in (8.000 cm)
Package 2 Width	3.35 in (8.500 cm)
Package 2 Length	8.66 in (22.000 cm)
Package 2 Weight	2.818 lb(US) (1.278 kg)
Unit Type of Package 3	S03
Number of Units in Package 3	48
Package 3 Height	11.81 in (30.000 cm)
Package 3 Width	11.81 in (30.000 cm)
Package 3 Length	15.75 in (40.000 cm)
Package 3 Weight	34.930 lb(US) (15.844 kg)

Offer Sustainability

Packaging without single use plastic	Yes
Packaging made with recycled cardboard	Yes
SCIP Number	F9865e0a-4be0-4110-b389-989cc9363cb0
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration

Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Take-back	No
Carbon footprint (kg CO2 eq, Total Life cycle)	34