

**Plugs and Bushings**

**1-1/4 INCH RECESSED PLUG**



**Catalog Number** PRPLG4  
**UPC** 784011209545

**Description**

PLG style plugs are used to close unused conduit hubs. They are available with either recessed square drive sockets or raised square drive heads.

**Application**

- Used to close unused conduit hubs

**Features**

- Used to close unused conduit hubs
- Available with recessed square drive sockets



**General Information**

|                 |  |
|-----------------|--|
| Trade Size      | 1-1/4  |
| Material        | FERROUS METAL  |
| Material        | FERROUS METAL  |
| Exterior Finish | Polyurethane coating on non-thread surfaces for corrosion protection |

**Dimensions**

|                         |     |
|-------------------------|-----|
| Nominal Weight (Pounds) | 0.3 |
|-------------------------|-----|

**Standards**

|         |  |
|---------|--|
| NEC/CEC | Class I, Division 1 & 2, Groups A, B, C, D |
| NEC/CEC | Class II, Division 1, Groups E, F, G       |
| NEC/CEC | Class III                                  |
| NEC/CEC | Class II, Division 2, Groups F, G          |

**Technical Specification Documents**

---

|                                   |                      |
|-----------------------------------|----------------------|
| Specification Guide (1995 Master) | AVAILABLE ON WEBSITE |
| Specification Guide (2004 Master) | AVAILABLE ON WEBSITE |
| Installer Certification and Tools | AVAILABLE ON WEBSITE |
| Chemical Resistance Charts        | AVAILABLE ON WEBSITE |
| Performance Specifications        | AVAILABLE ON WEBSITE |

### Technical Information

---

|                       |                    |
|-----------------------|--------------------|
| Fitting Configuration | RECESSED           |
| Fitting Type          | PLUG               |
| Product Category      | FITTING            |
| Product Family        | Plugs and Bushings |

### Notes

---

- All REC, RE, and PLGs meet Class I, Division 1 & 2, Groups C, D. REs & PLGs meet the above standards only when used in conjunction with hazardous location fittings.
- Suitable for Group B.