



P600WU | PROFESSIONAL SURGE PROTECTOR

Protect home and office computers, electronics, and home theater equipment

The P600WU Surge Protector Wall-tap with USB safeguards common home and office devices, such as computers and electronics, by absorbing spikes in energy caused by storms and electrical power surges. It provides 1,200 joules of protection, has 6 surge-protected outlets, and a wall-tap plug. Two USB ports (3.1 Amp shared) charge personal electronics, including smartphones, digital cameras, MP3 players, and other devices. The P600WU also features EMI/RFI noise filtering, power status indicators, and an impact-resistant casing.

The P600WU also features metal oxide varistor (MOV) technology, an EMI/RFI noise filter, a status indicator, and impact-resistant casing. This surge protector wall-tap comes with a 1-Year Limited Warranty and a Connected Equipment Guarantee.



TYPICAL APPLICATIONS

- Mobile Devices
- Personal Electronics
- Cell Phones
- Personal Computers

FEATURES

- Surge suppression: 1,200 J
- Volts: 125 V
- Circuit breaker: 15 A
- Plug type: NEMA 5-15P
- Outlet type: 6 NEMA 5-15R
- Power cord: Wall-tap
- USB charge ports: 2
- LED indicator: Yes
- EMI/RFI Filtration: Yes
- Warranty: 1-Year Limited
- Connected Equipment Guarantee: \$100,000

SPECIFICATIONS

INPUT	
Circuit Breaker	None
Cord Length	Wall-tap
Input Plug Type	NEMA 5-15P
Maximum Input Current	15 A
Plug Style	Wall-tap

OUTPUT	
Outlet Type	6 NEMA 5-15R
Outlets - Total	6
USB Charge Port	Yes
USB Charge Port Amperage	3.1 Amps (Shared)
USB Charge Port Quantity	2
USB Charge Port Type	Type A
USB Charge Port Voltage	5 VDC

P600WU

PROFESSIONAL SURGE PROTECTOR

SPECIFICATIONS CONT.

SURGE PROTECTION & FILTERING	
Attenuation	32 dB
Clamping Voltage	500V (H-N, H-G, N-G)
Coax Protection RG6	None
EMI/RFI Filtration	150 KHz 100 MHz Yes
Maximum Surge Current	52,500 A
Maximum Surge Current H-G	15,000 A
Maximum Surge Current H-N	22,500 A
Maximum Surge Current N-G	15,000 A
Maximum Surge Voltage	6,000 V
Response Time	<1 Nanosecond
Surge Suppression (Joules)	1,200 J
MANAGEMENT & COMMUNICATIONS	
LED Indicators	Protected (green) Grounded (green)
PHYSICAL	
Color	White
Cord Management	No
Form Factor	Wall-tap
Form Factors Supported	Direct plug
Keyhole Mounting Slots	No
Material of Construction	Plastic
Safety Covers	No

DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	10.16 x 17.46 x 3.49 cm
Physical Dimensions - Width/Height/Depth (mm)	102 x 175 x 35 mm
Physical Dimensions - Width/Height/Depth (in.)	4 x 6.875 x 1.375 in.
Weight (kg)	0.27 kg
Weight (lb.)	0.60 lbs.
SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	17.78 x 22.53 x 6.35 cm
Shipping Dimensions - Width/Height/Depth (mm)	177.8 x 225.3 x 63.5 mm
Shipping Dimensions - Width/Height/Depth (in.)	7 x 8.87 x 2.5 in.
Shipping Weight (kg)	0.33 kg
Shipping Weight (lbs.)	0.73 lbs.
CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL1449 3rd Edition cUL
WARRANTY	
CEG Amount	\$100,000
Connected Equipment Guarantee	Lifetime
Product Warranty	1-Year Limited