

ALTV1224DC220 Series

DC CCTV Power Supplies

Altronix ALTV1224DC220 Series DC CCTV power supplies provide 12VDC or 24VDC distributed via eight (8) or sixteen (16) fused or PTC protected outputs with a total of 4A or 6A continuous supply current for powering CCTV cameras, heaters, and other video accessories.



ALTV1224DC220

Key Features

- Eight (8) or sixteen (16) fuse or PTC protected outputs
- 12VDC or 24VDC selectable voltage
- 4A or 6A supply current
- Surge protection
- AC Input and DC Output LEDs
- Power ON/OFF switch
- Spare fuses provided (all models with primary and/or secondary fuses)
- CE European Conformity
- Lifetime Warranty

ALTV1224DC220 Series Power Supply Configuration Reference Chart

Altronix Model Number	220VAC, 50/60Hz Input Current	Total Output Current (Power)	Output Current (max per output)	Number of Outputs	PTC Protected Outputs (auto-resettable)	Fuse Protected Outputs
ALTV1224DC220	0.9A	4A	3.5A	8	—	✓
ALTV1224DCCB220			2.5A		✓	—
ALTV1224DC1220			3.5A	16	—	✓
ALTV1224DC1CB220			2.5A		✓	—
ALTV1224DC2220	1.5A	6A	3.5A		—	✓
ALTV1224DC2CB220			2.5A		✓	—

Lifetime Warranty



ALTV1224DC220 Series

DC CCTV Power Supplies

Specifications

Input

Voltage 220VAC (working range 198VAC-256VAC),
50/60Hz.

Outputs

Voltage 12VDC or 24VDC selectable
Current Varies, see Reference Chart
Protection Fused 3.5A / PTC 2.5A

Indicators (LED)

Input 220VAC is present
Output DC output is powered

Battery Charging

Capacity 12VDC/7AH (2 within enclosure)
40AH/65AH (requires separate enclosure)
Type Sealed lead acid or gel type
Failover Upon AC loss, instantaneous
Batteries are sold separately

Agency Listings

CE European Conformity

Physical and Environmental

Dimensions (H x W x D)

Enclosure:
13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.6mm)
Shipping:
15" x 13.875" x 4.75" (381mm x 352.4mm x 120.6mm)

Weight (approx.)

Model	Product Weight	Shipping Weight
ALTV1224DC(CB)220	7.8 lb. (3.54 kg)	8.7 lb. (3.95 kg)
ALTV1224DC1(CB)220	7.9 lb. (3.58 kg)	8.8 lb. (3.99 kg)
ALTV1224DC2(CB)220	7.9 lb. (3.58 kg)	8.8 lb. (3.99 kg)

Temperature

Operating: 0°C to 49°C (32°F to 120°F)
Storage: - 20°C to 70°C (- 4°F to 158°F)

Relative Humidity 85% +/- 5%
BTU/Hr. (approx.)

Model	12VDC	24VDC
ALTV1224DC(CB)220	25	49
ALTV1224DC1(CB)220		
ALTV1224DC2(CB)220	37	75

Lifetime Warranty

Altronix Corporation | 140 58th St | Brooklyn, NY 11220 USA
phone: +1 718.567.8181 | fax: +1 718.567.9056 | email: info@altronix.com | www.altronix.com




ALTV1224DC220 Series

DC CCTV Power Supplies

Dimensions and Drawing

Dimensions (H x W x D approximate)

13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.6mm)



Lifetime Warranty

Altronix Corporation | 140 58th St | Brooklyn, NY 11220 USA

phone: +1 718.567.8181 | fax: +1 718.567.9056 | email: info@altronix.com | www.altronix.com