



SINGLE-HOLE FAUCET
DEMD-101 – Battery

- For cold or premixed water
- Above deck solenoid and battery
- 0.5 gpm (1.9 L/min) vandal-resistant wrench flat spray outlet



SINGLE-HOLE FAUCET
DEMD-111 – Battery

- With side mixer
- Above deck solenoid and battery
- 0.5 gpm (1.9 L/min) vandal-resistant wrench flat spray outlet



SINGLE-HOLE FAUCET
DEMD-201 – Battery

- For cold or premixed water
- 0.5 gpm (1.9 L/min) vandal-resistant wrench flat spray outlet



SINGLE-HOLE FAUCET
DEMD-211 – Battery

- With side mixer
- 0.5 gpm (1.9 L/min) vandal-resistant wrench flat spray outlet



SINGLE-HOLE FAUCET
DEMD-301 – Battery

- Pre-mixed water by others
- Forged brass body
- 0.5 gpm (1.9 L/min) vandal-resistant flow control spray outlet



SINGLE-HOLE FAUCET
DEMD-311 – Battery

- Side mixer to adjust water temperature
- Forged brass body
- 0.5 gpm (1.9 L/min) vandal-resistant flow control spray outlet



SINGLE-HOLE WALL MOUNT FAUCET
DEMD-402 (8.0" Spout) – Hardwire
DEMD-404 (6.0" Spout) – Hardwire

- Tempered water supply by others
- Forged brass body
- 0.5 gpm (1.9 L/min) vandal-resistant flow control spray outlet
- Transformer required, order separately
- No conversion to battery possible



SINGLE-HOLE ELECTRONIC SOAP DISPENSER
DESD-550 – Battery, All-Cast Body
DESD-250 – Battery, Non-Metal Version

- Solid machined shank with low profile spout
- Standard 800 ml soap bottle
- Fits on decks up to 2" thick
- LED indicators: Yellow = low battery, Red = low soap
- Hardwire kit available

To convert faucets on this page from battery to hardwire, order the 060958A plug-in transformer (120 VAC to 9 VDC) or the 060974A converter (24 VAC to 9 VDC) – the latter requires a transformer by others.



OPTIONAL REMOTE CONTROL
060967A

- The sensor and flow time settings for the faucets on this page can be adjusted with this optional remote control. Can also be used with DEMD-86505 (Electronic Washdown Urinal Flush Valve), shown on page 29.