



GRAB-N-GO LEVELING PROGRAM

Get your setup dialed in with Lippert's lineup of leveling and stabilization essentials. From quick level checks to secure parking and added support, these tools help you create a safer, more stable campsite.



LEVEL WITH CONFIDENCE, ANYWHERE

Bubble Levels



Lippert bubble levels deliver precise leveling for a variety of surfaces with high-quality black ABS construction and a clearly visible digital scale.

Chocks



The Lippert plastic wheel chock keeps your vehicle or trailer securely in place with a non-slip surface and heavy-duty plastic construction. Its compact design is easy to carry and store for any trip.

Stackers



Lippert stacking leveling blocks provide safe, stable leveling for RVs and trailers with a 5,000-lb. capacity. The 10-block set and carry bag make setup, transport, and storage simple and reliable.

Curved Levelers



Lippert curved levelers provide fast, reliable leveling for trailers with heavy-duty construction and a complete accessory kit. Anti-slip pads and chocks enhance stability for safe setup on any terrain.

Pads



Lippert plastic jack pads provide reliable support and stability for stabilizer jacks, preventing sinking on soft surfaces. Their durable plastic construction and compact design make them easy to transport, position, and use.

Part #	Description
Bubble Levels	
2024121199	2pc Magnetic Cross Check Bubble 2.3"x1.7"
2025022179	2pc Rectangle Precision Bubble Levels 3.8"x1.4"
2024121200	3pc 1.25" Round Bubble Levels
Chocks	
2024121201	Plastic Regular with Rope, Black 8.2"x4.75"x4.33"
2025022180	Plastic Large with Rope, Black 10"x8.2"x5.3"
2024121202	Rubber Heavy Duty 8"x6"x4"
Stackers	
2024121204	10pk stacking (interlocking) leveling blocks - 8.5" square size, with carry bag
Curved Levelers	
2024121206	2pk curved leveler - including 2 curved pieces, 2 chocks, 2 anti-slip pads, and 1 carry bag
Pads	
2024121197	4pk interlocking plastic jack pads 6" square, 1" height, and carry strap
2024121198	4pk interlocking plastic jack pads, 14"L x 12"W x 0.86"H, and carry strap