

Cam-Type

18 Series Ball Nose Devices - 400A, 600V AC/DC Max NEMA 3R Rated for Outdoor Use

Male Plug - Double Set Screw Termination
(18D24-UE Shown)



Female Plug - Double Set Screw Termination
(18D33-UR Shown)



Male Plug - Single Set Screw Termination Contact
(From 18D21-U* Shown)



Female Plug - Single Set Screw Termination Contact
(From 18D29-U* Shown)



Male Panel Mount Receptacle - 7/8" Threaded Stud
(18R21-UB Shown)



Female Panel Mount Receptacle - Double Set Screw
(18R24-UG Shown)



Male Panel Mount Receptacle - Double Set Screw
(18R23-UH Shown)



Female Terminal Connector - Angled
(18F21-UW Shown)



Female Terminal Connector - Offset
(18F22-UE Shown)



18 Series Devices

Male Protective Cap
(18P21-UG Shown)



Female Protective Cap
(18P22-UB Shown)



Paralleling Tee Adapter
(18A21-UE Shown)



Tapping Tee Adapter
(18A22-UO Shown)



3-Fer (MFFF) Adapter
(18A23-UE Shown)



Double Female Adapter
(18A24-UE Shown)



Double Male Adapter
(18A25-UR Shown)



Cam-Type

18 Series Device Ordering Information

CAM-TYPE PLUGS

		Single Set Screw Termination [®] [®]		Double Set Screw Termination [®] [®]	
		Male Plug	Female Plug	Male Plug	Female Plug
Cable Size: #2 - 2/0 Max Ampacity: 300A Voltage: 600V AC/DC UL/CSA 1691 Listed	White	18D21-UW	18D29-UW	18D22-UW	18D31-UW
	Black	18D21-UE	18D29-UE	18D22-UE	18D31-UE
	Brown	18D21-UH	18D29-UH	18D22-UH	18D31-UH
	Red	18D21-UR	18D29-UR	18D22-UR	18D31-UR
	Blue	18D21-UB	18D29-UB	18D22-UB	18D31-UB
	Orange	18D21-UO	18D29-UO	18D22-UO	18D31-UO
	Green	18D21-UG	18D29-UG	18D22-UG	18D31-UG
	Yellow	18D21-UY	18D29-UY	18D22-UY	18D31-UY

		Single Set Screw Termination [®] [®]		Double Set Screw Termination [®] [®]	
		Male Plug	Female Plug	Male Plug	Female Plug
Cable Size: 2/0 - 4/0 Max Ampacity: 400A Voltage: 600V AC/DC UL/CSA 1691 Listed	White	18D23-UW	18D32-UW	18D24-UW	18D33-UW
	Black	18D23-UE	18D32-UE	18D24-UE	18D33-UE
	Brown	18D23-UH	18D32-UH	18D24-UH	18D33-UH
	Red	18D23-UR	18D32-UR	18D24-UR	18D33-UR
	Blue	18D23-UB	18D32-UB	18D24-UB	18D33-UB
	Orange	18D23-UO	18D32-UO	18D24-UO	18D33-UO
	Green	18D23-UG	18D32-UG	18D24-UG	18D33-UG
	Yellow	18D23-UY	18D32-UY	18D24-UY	18D33-UY

CAM-TYPE PANEL MOUNT RECEPTACLES

		.75" L Threaded Stud Termination [®] [®]	
		Male, 90°	Female, 90°
Cable Size: #2 - 4/0 Max Ampacity: 400A Voltage: 600V AC/DC UL/CSA 1691 Listed	White	18R21-UW	18R22-UW
	Black	18R21-UE	18R22-UE
	Brown	18R21-UH	18R22-UH
	Red	18R21-UR	18R22-UR
	Blue	18R21-UB	18R22-UB
	Orange	18R21-UO	18R22-UO
	Green	18R21-UG	18R22-UG
	Yellow	18R21-UY	18R22-UY

		Double Set Screw Termination [®] [®]	
		Male, 90°	Female, 90°
Cable Size: 2/0 - 4/0 Max Ampacity: 400A Voltage: 600V AC/DC UL/CSA 1691 Listed	White	18R23-UW	18R24-UW
	Black	18R23-UE	18R24-UE
	Brown	18R23-UH	18R24-UH
	Red	18R23-UR	18R24-UR
	Blue	18R23-UB	18R24-UB
	Orange	18R23-UO	18R24-UO
	Green	18R23-UG	18R24-UG
	Yellow	18R23-UY	18R24-UY

Note: Some items may require extended lead times; always consult with your local sales representative for current availability.