

XP-PSM-S



CommScope XPND™ Singlemode Splice Cassette, stranded, 24 LC/APC

- Can be installed and removed from front or rear of panel

Product Classification

| | |
|------------------------------|--|
| Regional Availability | Latin America North America Asia Australia/New Zealand |
| Product Type | Fiber cassette with pigtails |
| Product Brand | CommScope XPND™ |

General Specifications

| | |
|-------------------------------|------------------|
| Adapter Color | Green |
| Color, front | Green |
| Interface, front | LC/APC |
| Interface, rear | Stranded pigtail |
| Total Fibers, quantity | 24 |
| Total Ports, quantity | 24 |

Dimensions

| | |
|---------------|-----------------------|
| Height | 19 mm 0.748031 in |
| Width | 202.5 mm 7.97244 in |
| Depth | 207 mm 8.14961 in |

Optical Specifications

| | |
|-------------------|------------|
| Fiber Mode | Singlemode |
| Fiber Type | G.657.A1 |

XP-PSM-S

Environmental Specifications

| | |
|------------------------------|--------------------------------------|
| Operating Temperature | -40 °C to +70 °C (-40 °F to +158 °F) |
| Storage Temperature | -40 °C to +70 °C (-40 °F to +158 °F) |

Packaging and Weights

| | |
|---------------------------|---|
| Packaging quantity | 1 |
|---------------------------|---|

Regulatory Compliance/Certifications

| Agency | Classification |
|---------------|-----------------------------------|
| CHINA-ROHS | Below maximum concentration value |
| ROHS | Compliant |
| UK-ROHS | Compliant |

