


DUO AC-LED COLOR OPTION LIGHT BARS



BA-ACLED



PRODUCT DESCRIPTION

Bringing out the best in bold, eye-catching residential, retail and commercial displays, DUO AC-LED COLOR OPTION Light Bars are ideal for counters and cabinets. Thermally efficient, these fixtures are crafted for illuminating heat sensitive perishables and color sensitive apparel, artwork and collectibles.

FEATURES

- High CRI 90+
- Does not require any driver or transformer
- True 1" profile
- Backlighting with parabolic reflector allows a high uniformity of light
- Each light bar includes one "I" connector
- Minimal space between diffusers for a visually seamless line of illumination
- Free of projected heat, UV and IR radiation
- 54,000 hour rated life
- 5 year WAC Lighting product warranty

SPECIFICATIONS

- Construction:** Extruded aluminum body with polycarbonate lens.
- Power:** Direct 120VAC 60Hz input.
- Light Source:** 2700K and 3000K AC LEDs. CRI: 90.
- Dimming:** May be dimmed down to 10% with electronic low voltage (ELV) dimmer. Compatible with **LUTRON DVELV-300, SELV-300** Electronic Low Voltage dimmer
- Finish:** Abrasion resistant Bronze (BZ), Brushed Aluminum (AL) and White (WT) powder coat.
- Standards:** ETL & cETL Listed, Title 24 JA8 Compliant

ORDER NUMBER

Model#	Length	Color Temp	Finish
BA-ACLED	8 8"	27/30 2700K and 3000K	BZ Bronze AL Brushed Aluminum WT White
	12 12"		
	18 18"		
	24 24"		
	30 30"		
	36 36"		
	42 42"		

BA-ACLED -

Example: **BA-ACLED12-27/30AL**

Fixture Type:

Catalog Number:




Project: _____

Location: _____


FIXTURE PERFORMANCE

Model #	Color Temp	Power	Lumens	Efficacy
BA-ACLED8-27/30	2700K and 3000K	6.0W	330	55 Lm/W
BA-ACLED12-27/30		8.0W	475	59 Lm/W
BA-ACLED18-27/30		10.0W	545	55 Lm/W
BA-ACLED24-27/30		15.0W	930	62 Lm/W
BA-ACLED30-27/30		17.5W	1095	63 Lm/W
BA-ACLED36-27/30		19.5W	1305	67 Lm/W
BA-ACLED42-27/30		22.5W	1445	64 Lm/W

ACCESSORIES

6' power cord 	BA-PC6-WT	Supplies power in any application.
"I" connector 	BA-I-WT	Interconnection for seamless end to end transitions. One included with each light bar.
Interconnect cable 	BA-IC12-WT BA-IC24-WT BA-IC36-WT	12" 24" 36" Links two light bars using a single power connection.

FINISHES



wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters, East Manufacturing Facility

44 Harbor Park Drive

Port Washington, NY 11050

South East Manufacturing Facility

1600 Distribution Ct

Lithia Springs, GA 30122

Central Manufacturing Facility

1700 South J Elmer Freeway, Ste 100

Cedar Hill, TX 75104

West Manufacturing Facility

1750 S Archibald Ave

Ontario, CA 91761