



WINDOW AIR CONDITIONER

WITH HEAT | 18,800 BTU | ELECTRONIC




4PACH18000

UPC CODE	842149000561
COOLING CAPACITY (BTU)	18,800
HEATING CAPACITY (BTU)	16,000
ENERGY STAR	No
COVERAGE AREA (sq. ft.)	1,000
CEER	10.7
VOLTAGE	208/230V
AMPS	9.8/10.8
WATTS	1760/1720
WINDOW WIDTH (min/max) (in.)	28-40.5
WINDOW HEIGHT (min) (in.)	18.5
FAN SPEEDS (cool/fan/heat)	3/3/1
UNIT DIMENSIONS (W×H×D) (in.)	25.5×18×23.75
PKG. DIMENSIONS (W×H×D) (in.)	30×19.5×26
WEIGHT (Net/Gross) (lbs.)	117.25/131.75
CONTAINER QTY. (40HQ)	270
REFRIGERANT	R32
OUTLET CONFIGURATION	 30A - 230V

CHOOSING THE RIGHT AIR CONDITIONER

1 MEASURE AREA OF THE ROOM



2 MATCH ROOM SIZE WITH CORRECT BTUs

SQ. FT.	ROOM SIZE	BTUs
150	10' x 15'	5,000
250	10' x 25'	6,000
350	17' x 20'	8,000
450	15' x 30'	10,000
550	20' x 27'	12,000
700	20' x 35'	14,000
1,000	25' x 40'	18,000
1,500	30' x 50'	25,000

3 MAKE ANY ADJUSTMENTS



INCREASE BTU 10% FOR SUNNY ROOMS. DECREASE BTU 10% FOR SHADED ROOMS.




ADD 600 BTUs FOR EACH ADDITIONAL PERSON OVER TWO.



ADD 4,000 BTUs IF UNIT IS USED IN A KITCHEN.

4 MEASURE WINDOW OPENING (HEIGHT & WIDTH)



FEATURES

- 3 cooling and fan speeds & 1 heat speed
- 4-way adjustable air vents
- Cool, Heat, Fan, Eco, and Sleep modes
- Quick & easy installation
- Mounting kit included
- Electronic controls
- Follow-me remote control acts as portable thermostat
- 24-hour timer
- Auto-restart
- Adjustable thermostat (62-86°F)
- Easy clean tilt-out filter

